

QuickScan® QS2500

Data Sheet

Linear Imager



Mechanical

Dimensions
 Height: 18.5 cm / 7.3"
 Width: 7.4 cm / 2.9"
 Length: 11.4 cm / 4.5"
Weight: 179 g / 6.3 oz. (cable not included)

Environmental

Temperature Rating:
Operating: 0° to 45° C / 32° to 113° F
Storage: -30° to 65° C / -22° to 149° F

Humidity:

Operating: 5 to 95% NC
Shock: Withstands ten 1.5m (5.0') drops to concrete
Water & Dust: Resistant, IEC 60529 rating IP42DW
ESD Protection: Functional after 15kV discharge

Optical

Light Source: 660nm Visible Red Diode
Scan Rate: 200 scans/sec
Scan Width: 10.2 cm/4.0" at 12.7 cm/5.0" from label
Resolution: 0.13mm / 5 mils
Print Contrast: 25% or higher
Pitch: ±60°
Skew: ±75°
Scan angle: 46°

Ambient Light Immunity

Artificial Light: 75,000 Lux / 6,968 foot candle
Sunlight: 75,000 Lux / 6,968 foot candle

Depth of Field: Refer to table below

DEPTH OF FIELD*	
Range Comparisons	
LABEL DENSITY	RANGE
5 mils	2.5 - 11.4 cm / 1.0" - 4.5"
10 mils	1.3 - 21.6 cm / 0.05" - 8.5"
13 mils (100% UPC)	1.3 - 28.0 cm / 0.5" - 11"
20 mils	2.5 - 40.6 cm / 1.0" - 16"
40 mils	5.0 - 71.0 cm / 2.0" - 28.0"

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Accessories



P/N: 7-0803 (Gray);
 P/N: 7-0832 (Black)
 Hands Free Stand

P/N: 7-0393
 Tabletop or
 Wall Mount

Electrical

Operating Current:
Operating: 225 mA @ 5 VDC
Standby: 100 mA @ 5 VDC

Communications

- RS-232
- Keyboard Wedge
- Wand Emulation
- USB
- IBM 46XX
- IBM USB

Decoding Capability (autodiscriminates)

- UPC A, E / EAN 8, 13 / JAN 8, 13 (Including add-ons P2/P5)
- Code 128
- Pharmacode 39
- Codabar
- Industrial 2 of 5
- RSS-14
- RSS Expanded
- MSI/Plessey
- Telepen
- Code 11
- Code 93
- Code 39
- Interleaved 2 of 5
- Matrix 2 of 5
- RSS-14 Stacked
- RSS Limited
- UK/Plessey
- Code 16K
- PDF-417 with audio assist

Safety & Regulatory

Electrical: Complies to UL and cUL
Emissions: Complies to FCC-A; EN 55022-B; VCCI-A
Laser Classification: IEC 60825 Class 1 LED
Restriction of Hazardous Substances: Complies to EU RoHS



Ideal for:

- Retail applications
- Health care
- Inventory
- Office automation
- Document tracking
- Light industrial

Features:

- Aggressive reading and an extended depth-of-field
- Reads Reduced Space Symbology (RSS), PDF-417 and linear codes for flexibility
- Ergonomic "aim and shoot" design
- Reliable and durable, providing long lasting performance



Datalogic Scanning, Inc.
 Toll free: 1 800 695 5700
 International: 1 541 683 5700
 E-mail us at: scanning@datalogic.com
www.datalogic.com



Copyright © Datalogic Scanning, Inc. 2002-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic S.p.A. • All brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.datalogic.com. • Product specifications are subject to change without notice.