

QuickScan® QS6500

Linear Imager

Data Sheet



Mechanical

Dimensions

Height: 16.5cm / 6.0"

Width: 7.4cm / 2.9"

Length: 9.9cm / 3.9"

Weight: 181.4 g / 6.4 oz

Environmental

Temperature Rating

Operating: 0° to 50°C / 32° to 122° F

Storage: -40° to 70° C / -40° to 158° F

Humidity:

Operating: 5 to 95% NC

Storage/Transport: 5 to 95% NC

Vibration: Meets MIL STD-810E

Mechanical Shock: Withstands 50 drops from 15m / 5' to concrete

ESD Protection: Functional after multiple 25kv discharges.

Water & Dust: IEC529 Rating IP52DW

Electrical

Operating Voltage: +4.5 to 14VDC ±5%

Operating Current: 300mA @ 5VDC

Idle Current: 200mA @ 5VDC

Optical

Ambient Light Immunity

Artificial & Sunlight: 86,000 Lux

Light Source: 630nm Visible Red Diode

Scan Rate: 450 scans/sec max

Sensor: 2048 pixel linear imager

Scan Width: 16.5cm / 6.3" @ 17.8cm / 7" from nose

Resolution: 5 mils / .13mm

Print Contrast: 30% or greater

Pitch: ±60°

Skew: ±55°

Depth of Field: Refer to Chart below

Features:

- Aggressive linear imaging performance with up to 38 cm / 15" reading on 100% UPC labels
- Supports RSS and PDF-417 for future industry compatibility
- 2005 Sunrise compliant
- Multi-interface solution supports all popular host terminal interfaces
- Flash memory for easy software upgrades
- Built tough to withstand common POS abuse for many years
- Attractive, yet durable design to complement your point-of-sale

DEPTH OF FIELD Range Comparisons		
LABEL DENSITY	RANGE*	
	1D MODELS	PDF MODELS
5 mil Linear	51-127 cm / 2.0 - 50"	5 - 11.4 cm / 2.0 - 4.5"
7.5 mils	2.5 - 17.8 cm / 1.0 - 70"	2.5 - 16.2 cm / 1.0 - 6.0"
10 mils	0 - 30.5 cm / 0 - 12"	0 - 26.7 cm / 0 - 10.5"
13 mils / 100% UPC	0 to 38 cm / 0 - 15"	0 - 33 cm / 0 - 13"
20 mils	Up to 61.0 cm / 24"	Up to 53.3 cm / 21"
40 mils	Up to 101.6 cm / 40"	Up to 89 cm / 35"

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Decoding Capability

1D Versions

- UPC A, E / EAN 8, 13 / JAN 8, 13
- Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- RSS-14, Expanded, Stacked, Limited
- ISBN / Bookland EAN
- Code 39 (with full ASCII)
- Pharmacode 39
- Code 128
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- IATA
- Code 16K
- Code 11
- Codabar/NW7
- UK/Plessey
- MSI/Plessey

PDF Models support these additional symbologies:

- RSS Composites
- PDF-417
- Micro-PDF

Communications

- RS-232
- Keyboard Wedge
- IBM 46XX
- IBM USB
- USB

Safety & Regulatory

Electrical: Complies to EN60950, CSA60950, UL60950

Emissions: Complies to: FCC-A; EN 55022-B; BSMI 13438; AS/NZS 3548; VCCI-B, ICES-003

Laser Classification: IEC 60825 Class 1 LED

Restriction of Hazardous Substances: Complies to EU RoHS



DATALOGIC™

Datalogic Scanning, Inc.

Toll free: 1 800 695 5700

International: 1 541 683 5700

E-mail us at: scanning@datalogic.com

www.datalogic.com



Copyright © Datalogic Scanning, Inc. 2005-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic SpA. • All brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.datalogic.com. • Product specifications are subject to change without notice.