


# Symphone N2S

Android Smartphone PDA



## Features

### Powered by a Newland scanning module.

The N2S is armed with a high performance 1D/2D scanning module, ideal for day in and day out heavy scanning.

### First time everytime barcode scanning.

The N2S has a 25 degree scan angle, making scanning easy and comfortable while reading the screen.

### Built to withstand heavy use.

A durable design, reinforced by carefully selected materials, guarantees low maintenance costs even for use in harsh conditions.

### High quality PCAP Touch.

The N2S supports both dry and moist hands, as well as gloved fingertip touch input. Ideal for use in severe conditions, such as rain, snow and dust.

### Supplied with Symphone N2S charging stand.



## Application Scenarios

Warehouse management, Inventory counting, manufacturing, access control, back office inventory management, stock management, food traceability..

# Symphone N2S

## Android Smartphone PDA

Physical Specifications	Model	N2S	
	Dimensions	169*72*23.8mm	
	Keys	Front: Number keys, Five-navigation key, Back key, Del key Enter/End key, Dial key, Self-definition (F1, F2, F3) keys Sides: Power key, Left-scan key, Right-scan key, Function key	
	Input	English, pinyin, handwriting, soft-keyboard	
Product	OS	Android 5.1	
Performance	CPU	Dual-core 1.2 GHz	
	Screen	IPS, 3.5 inch WVGA, 480*800 pixel	
	Touch	Multi-point PCAP (Projective Capacitive Touch)	
	Memory	ROM	4GB
		RAM	1GB
Barcode Scanning	1D	Code39, Codabar, Code128, Interleaved 2 of 5, UPC, EAN, MSI and more	
	2D (optional)	QR, PDF417, DataMatrix, MaxiCode and more	
Network	Wi-Fi	IEEE 802.11 b/g/n	
	WCDMA/GSM	WCDMA: 2100 MHz GSM: 900 MHz, 1800 MHz	
	Bluetooth	BT 3.0 + HS, BT v2.1 + EDR	
	Camera	High-definition, auto focus	
	GPS	GPS, AGPS	
Battery	Capacity	4000mAh	
Endurance	Standby	500 hours	
	Talking	20 hours	
Ports & Accessories	T-Flash	Micro SD/TF (up to 32 GB)	
	SIM	Mini-SIM card	
	Jack	Micro USB, 3.5mm Audio jack, DC jack	
	Charging stand (included)	Charges device and battery at the same time	
	Others	Printer (optional) supports BT-connected devices, Adapter, Cable, Belt	
Certificates & Protection	Industrial protection	IP64	
	Certificates	CTA, CCC, CE, RoHS	
	Laser Safety	IEC2 / FDA II, IEC60825 / EN60825-1	

\*Specifications are subject to change without notice.\*

Version: V1.0

Newland EMEA  
+31 (0) 345 87 00 33  
info@newland-id.com

Newland D-A-CH  
+49 (0) 294 298 76758  
info@newland-id.de

Newland UK  
+44 (0) 1442 212 020  
sales@newland-id.co.uk

Newland Nordic & Baltic  
+46 (0) 708 847 767  
nordic@newland-id.com

Newland Ibérica  
+34 (0) 93 303 74 66  
info@newland-id.es

Newland France  
+31 (0) 345 87 00 33  
france@newland-id.com

Newland Middle East  
+31 (0) 345 87 00 33  
middleeast@newland-id.com

Newland South Africa  
+27 (0) 11 553 8010  
info@newland-id.co.za

Newland Italy  
+39 (0) 342 056 2227  
italy@newland-id.com

Newland Russia  
+31 (0) 345 87 00 33  
russia@newland-id.com