

TSP828L Thermal Label Printer

Features

- Ultra High Speed: 50LPS (150mm/sec.)
- High-Reliability
- Adjustable label widths from 1.75" to 4.4"
- "Drop In & Print" label loading
- Built-In Label Peeler with rear liner exit
- Auto-sense batch or peeler printing
- Black mark, die-cut label gap and registration hole media sensing
- High-Quality Barcode printing
- Standard Dual Interface USB/RS232 Serial
- Swappable interfaces for easy integration
- Space efficient wall and vertical mounts available
- Drivers available for: Windows 9x, 2000, XP, and Linux

The TSP828L sets the standard when it comes to desktop label printing. With the TSP828L, **Star** meets the **high quality**, ease-of-use demands of the entry-level thermal label printer market.

The TSP828L is perfect for all of your printing applications, from **shipping and receiving**, to **healthcare** and **jewelry**. The TSP828L can accommodate various label formats, and widths. The **built-in peeler** will speed you through your print jobs in an instant, and the rear exit liner ensures no worries of hassling with garbage. Print **batch** jobs or **auto-peel** your labels **without overlapping** thanks to the TSP828L's ability to sense when a label is still in the dispenser. When it's time to replace your labels, just drop them in and start printing, no need to feed or wind anymore! All of these features make the TSP828L the only true **clamshell** label printer available.

The TSP828L packs so much **value and performance** into a desktop label printer; you'll wonder why you would choose any other.



TSP828L shown with peeler and cover open



The TSP828 is ideal for:

- Shipping & Receiving
- Pizza Box/Delivery Labels
- Healthcare
- Photo Labeling
- Jewelry
- Retail
- Postal Services

Specifications		
Print Speed	50LPS (150mm/sec.)	
Paper Width	45 to 112mm (4.4")	
Print Width	104mm	
Resolution	203 dpi	
Print Columns	92/69	
Interface	Dual USB/RS232 Serial, Parallel,	
	Ethernet	
Emulation	Star Line/Page Mode	
Reliability	37 million lines MCBF	
Printer		
Power Supply	24 VDC (optional PS60A-24A)	
Case Color	Putty or Charcoal	
Drivers	Windows 9x/2000/XP, Linux	
Options	External power supply, wall & vertical	
	mount brackets	

All specifications are subject to change without notice.

The TSP828L is designed to easily fit into any existing application. The TSP828L works well with all the Industry leading software labeling applications such as BarTender \odot , NiceLabelTM, and LabelViewTM.

STAR TSP-828L Thermal Labels One Source, One Solution

Whatever your application, bar codes, shipping, medical, nutritional, retail or hospitality, Star supplies a full range of labels in a multitude of dimensions. Using Star labels assures you of an optimal quality label, with each and every print job.

Label Height	Label Width	Paper Width	Label Type
1.0 inch/26mm	3.0 inch/74.5mm	3.12 inch/79.5mm	Black Mark
3.9 inch/100mm	3.0 inch/	3	Gap
1.0 inch/26mm	3.0 inch/74.5mm	3.12 inch/79.5mm	Gap
4.0 inch/100.83mm	2.2 inch/56mm	2.34 inch/59.5mm	Gap
2.0 inch/50.88mm	3.0 inch/74.5mm	3.12 inch/79.5mm	Black Mark
1.0 inch/26mm	2.15 inch/54.5mm	2.34 inch/59.5mm	Gap
2.9 inch/74.37mm	3.0 inch/74.5mm	3.12 inch/79.5mm	Gap
2.0 inch/50.88mm	3.0 inch/74.5mm	3.12 inch/79.5mm	Gap
3.15 inch/80mm	4.15 inch/105mm	4.30 inch/110mm	Gap
6.0 inch/152.5mm	3.9 inch/100mm	4.15 inch/105mm	Gap