

LINEARLY POLARIZED GROUND ANTENNA SlimLine - A6590L

ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organizations to transform processes & reduce costs.

Our SlimLine range of antennas are unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form.

Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.

Times-7 Research Ltd 29 Railway Avenue Lower Hutt 5010 New Zealand

P: +64 4 974 6566

NORTH AMERICA P: +1 858 225 2214

EMEA

P: +31 411 62 29 49

E: info@times-7.com

www.times-7.com



Part of Times-7's exclusively unique range of ground antennas the A6590L is optimized for RFID deployments involving moving products, assets and people. From conference attendee & people tracking, retail presence aware / loyalty marketing, & race timing, the A6590L is ideal for situations where traditional side antennas are unsuitable or not optimzed for the application.

At just 8 mm / 0.3 in. thick, the durable, high performance A6590L is uniquely capable of lying flat on the ground within a doorway sized footprint, and can withstand payloads of over 200 kg (440 lb).

Ultra-low profile linear polarised UHF ground antenna

Just 8 mm / o.3 in. thick

Typical applications:

Conference attendee & people tracking,

retail marketing,

race & event timing

Specifications

Physical / Environmental Specifications

: iiyoroar, ziiiiioriiai opoomoarone		
Dimensions (L x W x D):	910 mm x 300 mm x 8 mm	
	3' x 1' x 0.3"	
Weight:	2 kg / 4.4 lbs.	
Radome Material:	Fire retardant ABS	
Environmental Rating:	IP65	
Operating / Storage Temperature:	-20° to +55°C / -30° to +65°C	
	-4° to +131°F / -22° to +149°F	
Connector type / position:	SMA female side fly lead (300 mm / 1')	
Cable:	2 m SMA to RPTNC (included)	

Electrical Specifications


Frequency Range:	864-869 MHz / 902-928 MHz	
Polarization:	Linear	
Far-field Gain:	10 dBi	
Far-field 3 dB beamwidth:	72° in XZ, 23° in YZ	
Typical VSWR across frequency range:	< 1.4:1	
Front to back ratio:	20 dB	
Nominal Impedance:	50 Ω	
Anti-static protection:	Yes	
Maximum Input Power:	6 W	






LINEARLY POLARIZED GROUND ANTENNA SlimLine - A6590L

E-field elevation & Azimuth Patterns





XZ-plane YZ-plane

Ordering Information (please quote both product code & part no.)

Product Code	Band	Part No.
A6590L	ETSI 864-869 MHz	71234
A6590L	FCC 902-928 MHz	71211
Cable Accessories	Cable Type	Part No.
Cable 2 m, SMA to RPTNC	195 / 240	71436 / 71782
Cable 4 m, SMA to RPTNC	195 / 240	71437 / 71784
Cable 8 m, SMA to RPTNC	195 / 240	71438 / 71788

Applications

- Conference Attendee / People Tracking
- Retail Presence Aware / Loyalty Based Marketing
- Race & Event Timing







The technical data contained in this publication is not a guarantee for which Times-7 Research Ltd assumes legal accountability. It is indicative of typical performance, and if required should be relied on for specific applications only after due verification.

All technical data, specifications and other information contained herein are deemed to be the proprietary intellectual property of Times-7 Research Ltd. No reproduction, copy or use thereof may be made without the express written consent of Times-7 Research Ltd.



Constantly increasing market reach and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.

Times-7 Research Ltd 29 Railway Avenue Lower Hutt 5010 New Zealand

> NZ + APAC P: +64 4 974 6566

NORTH AMERICA P: +1 858 225 2214

EMEA 2: +31 411 62 29 49

E: info@times-7.com

www.times-7.com

