


## L901 Industrial Color Label Printer



### Designed Specifically for Inline Applications


The L901 combines industrial design, exceptional image quality, and high production speeds with a new ability to service and maintain the printhead “on-the-fly.” This makes the L901 perfect for long roll-to-roll print jobs or inline integration with label finishers, applicators, dispensers, and more.

Producing vibrant full-color prints in high resolution, the L901's new optimized ink formula delivers improved UV and water resistance, deeper blacks, and a longer printhead life. Large print volumes are now more economical, with five high-capacity 250ml CMYKK ink cartridges delivering an ultra-low cost per label.

#### Key Features

- ✓ Designed for easy integration
- ✓ On-the-fly printhead servicing
- ✓ Lower cost per print
- ✓ High speed & resolution

#### Optimized for these inline uses:



Presses / Finishers



Roll to Roll



Print & Apply

#### New Optimized CMYKK Ink Formula

Increased UV and water resistance with deeper blacks, all at a new lower cost of ownership

#### Touchscreen Operation

Easily store, run and pause jobs, or perform maintenance tasks through a user-friendly interface

#### Industrial Build Quality

Designed for all-day operation—either roll-to-roll or inline—in a production environment

#### Professional-Quality Output

1600 DPI resolution delivers your jobs in style and on time, even with variable data



+1.888.215.3966  
[sales@afinialabel.com](mailto:sales@afinialabel.com)  
[afinialabel.com](http://afinialabel.com)



# L901 Specifications

## Printer:

<b>Print method:</b>	Memjet Waterfall Printhead Technology® 11 Integrated Circuit (IC) Chips – 70,400 nozzles
<b>Inks:</b>	Dye-based, 250mL CMYKK (1.25L total) — Water/UV resistant formula
<b>Print resolution:</b>	1600 x 1600 dpi – 1600 x 800 dpi
<b>Print speed:</b>	6 inches (152 mm) per second – 12 inches (305 mm) per second
<b>Print width:</b>	8.5 inches (216 mm)
<b>Cutter/sheeter:</b>	Powered

## Media:

<b>Media Size:</b>	Width: 2"–9" (50.8 mm–229 mm) Length: 1"–48" (25.4 mm–1220 mm)	<b>Media sensors:</b>	Gap (movable), continuous, black mark
<b>Thickness:</b>	Minimum 0.005" (0.13 mm) Maximum 0.01" (0.3 mm, including liner)	<b>Die-cut gap:</b>	Minimum 0.125" (3.0 mm) Maximum 0.3" (8.0 mm)
<b>Core diameter*:</b>	Requires 3" (76.2 mm) cardboard core	<b>Black mark:</b>	3 mm wide, 25.4 mm long on left
<b>Unwind/Rewind*:</b>	12" (305 mm) outside diameter	<b>Substrates:</b>	Compatible with a wide range of paper, polyester, polypropylene, and vinyl label stocks

*\*with optional XL Unwind/Rewind system, shown below*

## General:

<b>Interfaces:</b>	USB 2.0, TCP/IP (Manual IP configuration or DHCP), GPIO available for external device control
<b>Operating system:</b>	Windows 7, 8, and 10 (32 and 64 bit)
<b>Barcode font:</b>	1D Barcode at least Grade B (Code39) with 10mils bar width
<b>2D code printing:</b>	2D Barcode at least Grade B (PDF417) with 10mils cell size
<b>Operating temperature:</b>	15°–35° C (59°–95°F) at RH 20–80%
<b>Overall dimensions**:</b>	22.5" (572 mm) W, 20.5" (521 mm) D, 14" (356 mm) H
<b>Weight:</b>	85 lbs. (38.5 kg)
<b>Rated voltage:</b>	AC 110V – 220V, auto-sensing
<b>Warranty:</b>	One year

### Optional XL Unwind/Rewind System

For high-capacity roll-to-roll production.  
Visit our website or contact us for details.



**\*\*Dimensions with XL Unwind/Rewind System:**  
59.5" (1512 mm) W, 20.5" (521 mm) D, 23" (585 mm) H



**Label Printing Solutions for Every Level of Production**  
**AfiniaLabel.com**



+1.888.215.3966  
sales@afinialabel.com  
afinialabel.com

**AFINIA LABEL®**