

Standard types

Delivery program of self-adhesive Labels

Why labels from cab?

As a printer manufacturer, we know exactly what it takes to achieve the best possible printing results. The various surface options of our labels are optimised for high image fidelity in thermotransfer printing. The reel diameter, the core diameter and the winding are synchronised to cab printers. We deliver high quality labels made of well-established materials and in common sizes – always at a competitive price and in a fast manner, as we have most of these in stock.

Of course we also offer customer specific solutions. You can chose between more than 300 different materials of any size or shape – even with your individual text or graphic on. We are specialised in providing reliable labels for fully automated industrial applications.

Well-proven ribbons that match perfectly with our labels are of course part of our product range as well. We will be pleased to advise you which labels are the most suitable for your application. Phone: +49 721 /6626 0 | E-Mail: etiketten@cab.de



Paper white, slightly glossy, coated, 80 g/m²

This material is a standard label for multipurpose use. Permanent adhesive on acrylate base. This paper accores to the letter of recommendation BfR XXXVI (direct contact with dry and/or greasily food). All-purpose labels, suitable for logistics, industrial and packaging applications, as well as for labelling blisters, food, cosmetics and medical devices. We recommend the use of our wax or wax / resin ribbons to achieve the best possible printing results with any of the cab printers.

Service temperature: -30°C - +80°C
Minimum application temperature: -10°C

Paper white slightly glossy, coated, 80 g/m ²				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5556470	25	10	150	7.000
5556880	35	25	150	3.000
5556471	40	20	150	3.500
5556881	50	25	150	3.000
5556472	54	35,5	150	2.250
5556882	60	40	150	1.900
5556473	68	58	150	1.400
5556474	75	35	150	2.300
5556475	89	36	150	2.500
5556476	85	50	150	1.500
5556477	100	42	150	2.000
5556883	100	50	150	1.500
5556884	100	80	150	1.000
5556480	100	150	150	500
5556478	110	68	150	1.200
5556479	115	99	150	800
5556450	157	112	200	1.500
5556491	148	210	200	850
5556489	210	149	200	1.000



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended:
Wax: KWAXX/
W41/W42
Wax/Resin: RW62/B110A/
B110TI/M265

Standard types

Delivery program of self-adhesive Labels

Polypropylene, white matt, 0,057 mm

High-quality, biaxially oriented, corona pretreated polypropylene film. Ideal for permanent product labeling in the field of chemistry, body care, food and a great number of packaging materials. High resistance to water, oil and chemicals.

ISEGA and FDA approved for direct contact with dry, not-fatty food and for food packaging materials.

For standard applications low priced wax-resin transfer ribbons can be used. We recommend to use resin transfer ribbons for scratch-proof and permanent print results. We will be happy to advise you.

Operating temperature: -20 to +80 °C
Application temperature: min. +5 °C

Polypropylene (PP), white matt, 0,057 mm				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5780024	40	20	152	3.500
5780025	50	30	152	2.500
5780026	60	30	152	2.500
5780027	60	40	152	2.000
5780028	70	30	152	2.500
5780029	70	50	152	1.600
5780030	85	50	152	1.600
5780031	102	50	152	1.600
5780032	100	150	152	500
5780033	148	210	205	800

Part No. 5780033 not for EOS1



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended
Wax/Resin: B110A/RW62/M265
Resin: R71, R81, R81 R rot, B120EC

Polyester white matt, 0,050 mm

High class coated polyester foil with a thickness of 0,050 mm. Equipped with a permanently sticking acrylate adhesive. Suitable for all applications where a good resistance against water, oil or chemicals is important. We recommend the use of our resin ribbons to achieve excellent printing results - scratch-proof and permanent.

Service temperature: -20°C - +100°C
Min. application temperature: +5°C

Polyester white matt, 0,050 mm				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5556485	25	8	150	7.500
5556486	50	30	150	2.500
5556487	60	40	150	2.000
5556488	85	50	150	1.670



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended:
Resin: B120EC/R71/B110C/B110CX/AXR8/R510

Premium Polyester, white matt, 0,050 mm

Top quality, coated 0,050 mm polyester film with best value pricing. Durable, acrylate based adhesive.

For permanent industrial applications. Ideal for adhesion on metal, varnishes and plastics.

UL File MH16635. RoHS approval according to (2002/95/EC), IMDS data available on request.

We recommend to use resin transfer ribbons to achieve excellent scratch-proof and permanent print results.

Operating temperature: -40 to +150 °C
Application temperature: min. +10 °C

Premium Polyester, white matt, 0,050 mm				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5780034	25	8	152	8.000
5780035	40	20	152	3.500
5780036	50	30	152	2.500
5780037	60	30	152	2.500
5780038	60	40	152	2.000
5780039	70	30	152	2.500
5780040	70	50	152	1.600
5780041	85	50	152	1.600
5780042	102	50	152	1.600



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended:
Resin: B120EC/R71/B110C/B110CX/AXR8/R510

Standard types

Delivery program of self-adhesive Labels

Polyester silver matt, 0,025 mm

High class coated polyester foil with a thickness of 0,025 mm. Equipped with a permanently sticking acrylate adhesive. Suitable for all applications where a good resistance against water, oil or chemicals is important. We recommend the use of our resin ribbons to achieve excellent printing results - scratch-proof and permanent.

Service temperature: -20°C - +130°C
Minimum application temperature: +10°C

Polyester silver matt, 0,025 mm				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5556481	25	8	150	10.000
5556482	50	30	150	2.500
5556483	60	40	150	2.000
5556484	85	50	150	1.500



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended:
Resin: B120EC/R71/
B110C/B110CX/
AXR8/R510

Premium Polyester, silver matt, 0,050 mm

Top quality, coated 0,050 mm polyester film with best value pricing. Durable, acrylate based adhesive.

For permant industrial applications. Ideal for adhesion on metal, varnishes and plastics.

UL File MH 16635. RoHS approval according to (2002/95/EC), IMDS data available on request.

We recommend to use resin transfer ribbons to achieve excellent scratch-proof and permanent print results

Operating temperature: -40 to +150 °C
Application temperature: min. +10 °C

Premium Polyester, silver matt, 0,050 mm				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5780043	25	8	152	8.000
5780044	40	20	152	3.500
5780045	50	30	152	2.500
5780046	60	30	152	2.500
5780047	60	40	152	2.000
5780048	70	30	152	2.500
5780049	70	50	152	1.600
5780050	85	50	152	1.600
5780051	102	50	152	1.600



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended:
Resin: B120EC/R71/
B110C/B110CX/
AXR8/R510

Polyester silver matt, 3M 7818EH 0,081 mm

Top-quality coated polyester foil with a thickness of 0,081 mm. Equipped with a permanently sticking acrylate adhesive. For permanent and industrial applications. These labels can be applied to varnished and metallic surfaces, as well as to high-energy plastic surfaces. UL File MH18072. We recommend the use of our resin ribbons to achieve excellent scratch-proof and permanent printing results.

Service temperature: -40°C - +150°C
Minimum application temperature: +15°C

3M 7818 Polyester silver matt, 0,081 mm				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5556495	25	8	200	10.000
5556496	50	30	200	2.500
5556497	60	40	200	2.000
5556498	85	50	200	1.670



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

Ribbon recommended:
Resin: B120EC/R71/
B110C/B110CX/
AXR8/R510

not for EOS1

Standard types

Delivery program of selve-adhesive Labels

High-glossy inkjet labels

High-class, high-gloss paper for multicolor inkjet-print in high resolution. Optimally compatible to our color label printer cab LX900e.

You can create your own high quality product labels, labels for logistics, billboards, eye-catching image and seasonal labels, warning decals, information labels.

Water-based, permanent adherent acrylat-adhesive. Heat-resistant from -20°C up to 100°C

High-glossy Ink-Jet Labels				
Part No.	Width mm	Hight mm	Roll Ø mm	Labels on Roll
5556320	54	35,5	150	1.250
5556321	75	35	150	1.250
5556323	100	42	150	1.250
5556325	110	68	150	1.000
5556328	210	149	150	400



Adhesive: permanent
Winding: outside
Core Ø: 76 mm

All information on scopes of delivery, design and technical specifications correspond to the date of the printing. Subject to change. The data provided in the catalog do not represent any warranty or guarantee.

For current data see website www.cab.de/en/labels

Product overview

Label printers MACH1, MACH2
in the lower price segment



Label printers MACH 4S
where little space is available



Label printers EOS1
Desktop device for label rolls
up to diameter 152 mm



Label printers EOS4
Desktop device for label rolls
up to diameter 203 mm



Label printers SQUIX 2
Industrial device for print widths
up to 57 mm



Label printers SQUIX 4
Industrial device for print widths
up to 108 mm



Label printers SQUIX 6
Industrial device for print widths
up to 168 mm



Label printers A8+
Industrial device for print widths
up to 216 mm



Label printers XD4T
for double-sided printing



Label printers XC
for two-color printing



Print and apply systems Hermes+
for automation



Print and apply systems Hermes C
for two-color printing and applying



Print modules PX
to be integrated in labeling machines



Labels
made from more than 400 materials



Ribbons
in wax, resin and resin/wax qualities



Label software cablabel S3
Design, print, control



Label dispensers HS, VS
for horizontal or vertical dispense



Labeling heads IXOR
to be integrated in labeling machines




Marking lasers FL+
with output powers 10 to 50 Watt



Laser marking systems XENO 1
for single workpieces and series



 Headquarters and fabrication in Germany

 to  International subsidiaries

There are further 820 distribution partners in more than 80 countries.



Europe

Germany

cab Produkttechnik GmbH & Co KG
Wilhelm-Schickard-Str. 14
76131 Karlsruhe
phone +49 721 6626 0
fax +49 721 6626 129
info@cab.de
www.cab.de

France

cab Technologies S.à.r.l.
2a Rue de la Moder
Z.A. Nord du Val de Moder
67350 Niedermodern
phone +33 388 722501
fax +33 388 722502
info.fr@cab.de
www.cab.de/fr

America

USA

cab Technology, Inc.
21 Alpha Road, Suite 200
Chelmsford, MA 01824
phone +1 978 250 8321
fax +1 978 256 9564
info.us@cab.de
www.cab.de/us

Latin America

Alejandro Balmaceda
Hacienda Jurica Pte 1615
Colonial de Valle
32553 Juárez, Mexico
phone +52 656 682 4301
a.balmaceda@cab.de
www.cab.de/es

Asia

Taiwan

cab Technology Co., Ltd.
希愛比科技股份有限公司
16F-1, No. 700, Jhong Jheng Rd
Junghe, Taipei 23552
phone +886 (02) 8227 3966
fax +886 (02) 8227 3566
info.asia@cab.de
www.cab.de/tw

China

cab (Shanghai) Trading Co., Ltd.
铠博(上海)贸易有限公司
A507, No. 268, Tong Xie Rd
Shanghai 200335
phone +86 (021) 6236 3161
fax +86 (021) 6236 3162
info.cn@cab.de
www.cab.de/cn

cab (Shanghai) Trading Co., Ltd.
铠博(上海)贸易有限公司
Room 39, 10F, 8 Lin He Zhong Rd
Tian He District, Guangzhou 510610
phone +86 (020) 2831 7358
info.cn@cab.de
www.cab.de/cn

Africa

South Africa

cab Technology (Pty) Ltd.
8 Fabriek Street
Strijdom Park
Randburg 2169
phone +27 11 886 3580
fax +27 11 789 3913
info.za@cab.de
www.cab.de/za