



Panasonic recommends Windows.

TOUGHPAD FZ-G1

- 6th Generation Intel® Core™ i5 vPro™ Processor
- Daylight-readable Display with Gloved Multi Touch + waterproof digitizer pen
- Up to 28 Hours of Use with an Optional Long Life Battery¹
- Integrated Bridge Battery, SmartCard, 2D Barcode, Magstripe, RFID, Serial Options and More^{2,3}
- Certified for Use in Hazardous Locations (Class I Division 2)⁴
- 3-year Warranty with Business Class Support

4-FOOT
DROP RATING

IP65

MIL-STD-810G

THE WORLD'S THINNEST AND LIGHTEST FULLY RUGGED 10.1" WINDOWS 10 PRO TABLET

The Toughpad® FZ-G1 Windows 10 Pro tablet offers a fluid user experience while providing crucial port connectivity and feature-rich options in a compact size. Designed for highly mobile field workers, it's the thinnest and lightest fully rugged 10.1" tablet running Windows 10 Pro 64-Bit. Powered by an Intel® Core™ i5 vPro™ processor with a MIL-STD-810G and IP65 certified design, the Toughpad FZ-G1 Windows 10 tablet leads the way in rugged mobile computing. Add to that an HD daylight-readable 10-point gloved multi touch + waterproof digitizer pen, and it becomes an essential tool for field workers.

TOUGHPAD FZ-G1

Panasonic recommends Windows.

SOFTWARE	■ Windows 10 Pro 64 bit ■ Panasonic Utilities (including Dashboard), Recovery Partition														
DURABILITY	■ MIL-STD-810G certified (4' drop, shock, vibration, rain, dust, sand, altitude, freeze/thaw, high/low temperature, temperature shock, humidity, explosive atmosphere) ■ IP65 certified sealed all-weather design ■ Optional class I division 2, groups ABCD certified model ■ Solid state drive heater ■ Magnesium alloy chassis encased with ABS and elastomer corner guards ■ Optional hand strap or rotating hand strap ■ Port covers ■ Raised bezel for LCD impact protection ■ Pre-installed replaceable screen film for LCD protection														
CPU	■ Intel® Core™ i5-6300U vPro™ Processor – 2.4 GHz up to 3.0 GHz with Intel® Turbo Boost Technology – Intel Smart Cache 3MB														
STORAGE & MEMORY	■ 8GB DDR3L SDRAM^{4,5} ■ 256GB solid state drive (SSD) with heater^{4,5} ■ Optional 512GB – up to 64GB additional storage with optional microSDXC card slot														
DISPLAY	■ 10.1" WUXGA 1920 x 1200 with LED backlighting ■ 10-point capacitive multi touch + Waterproof Digitizer pen daylight-readable screen – 2-800 nit – IPS display with direct bonding – Anti-reflective and anti-glare screen treatments – Ambient light sensor, digital compass, gyro and acceleration sensors – Automatic screen rotation – Intel® HD Graphics 520 (Built-in CPU) video controller ■ Concealed mode (configurable)														
AUDIO	■ Integrated microphone ■ Realtek high-definition audio ■ Integrated speaker ■ On-screen and button volume and mute controls														
KEYBOARD & INPUT	■ 10-point gloved multi touch + digitizer screen – Supports bare-hand touch and gestures and electronic waterproof stylus pen – Supports glove mode and wet-touch mode ■ 7 tablet buttons (2 user-definable) ■ Integrated stylus holder ■ On-screen QWERTY keyboard														
CAMERAS	■ 720p webcam with mic ■ 8MP rear camera with autofocus and LED light														
EXPANSION	■ Optional MicroSDXC3														
INTERFACE	<table><tr><td>■ Docking connector</td><td>24-pin</td></tr><tr><td>■ HDMI</td><td>Type A</td></tr><tr><td>■ Headphones/speaker</td><td>Mini-jack stereo</td></tr><tr><td>■ Optional Serial Dongle³</td><td>D-sub 9-pin</td></tr><tr><td>■ USB 3.0 (x 1)²</td><td>4-pin</td></tr><tr><td>■ Optional second USB 2.0³</td><td>4-pin</td></tr><tr><td>■ Optional 10/100/1000 Ethernet³</td><td>RJ-45</td></tr></table>	■ Docking connector	24-pin	■ HDMI	Type A	■ Headphones/speaker	Mini-jack stereo	■ Optional Serial Dongle ³	D-sub 9-pin	■ USB 3.0 (x 1) ²	4-pin	■ Optional second USB 2.0 ³	4-pin	■ Optional 10/100/1000 Ethernet ³	RJ-45
■ Docking connector	24-pin														
■ HDMI	Type A														
■ Headphones/speaker	Mini-jack stereo														
■ Optional Serial Dongle ³	D-sub 9-pin														
■ USB 3.0 (x 1) ²	4-pin														
■ Optional second USB 2.0 ³	4-pin														
■ Optional 10/100/1000 Ethernet ³	RJ-45														
WIRELESS	■ Optional integrated 4G LTE multi carrier mobile broadband with satellite GPS ■ Optional GPS (u-blox NEO M8N)⁶ ■ Intel® Dual Band Wireless-AC 8260 (IEEE802.11a/b/g/n/ac) ■ Bluetooth v4.1, Classic mode/ Low Energy mode, Class 1 (Windows 10 pro 64-bit) ■ Security – Authentication: LEAP, WPA, 802.1x, EAP-TLS, EAP-FAST, PEAP – Encryption: CKIP, TKIP, 128-bit and 64-bit WEP, Hardware AES ■ Dual high-gain antenna pass-through														
POWER SUPPLY	■ Li-Ion battery pack: – Standard battery: Li-ion 11.1 V, 4200 mAh (typ.), 4080 mAh (min.) – Optional long life battery²: Li-ion 10.8V, 9300mAh(typ.), 8700mAh (min.) ■ Battery operation¹: – Standard battery: 14 hours – Optional long life battery²: 28 hours ■ Battery charging time¹: – Standard battery: 2.5 hours off, 3 hours on – Optional long life battery²: 3 hours off, 4 hours on ■ Optional bridge battery² (1 minute swap time)														
POWER MANAGEMENT	■ Suspend/Resume Function, Hibernation, Standby														
SECURITY FEATURES	■ Password Security: Supervisor, User, Hard Disk Lock ■ Kensington cable lock slot ■ Trusted platform module (TPM) security chip v.2.0¹² ■ Computrace® theft protection agent in BIOS8 ■ Optional Insertable SmartCard reader^{2,7} ■ Optional Contactless SmartCard/HF RFID reader² – ISO 15693 and 14443 A/B compliant														

WARRANTY

- 3-year limited warranty, parts and labor

DIMENSIONS & WEIGHT⁷

- 10.6"(L) x 7.4"(W) x 0.8"(H)
- 2.4 lbs. (standard battery)
- 3.0 lbs. (optional long life battery)⁷

INTEGRATED OPTIONS¹⁰

- 4G LTE multi carrier mobile broadband with satellite GPS
- Choice of 1D/2D barcode reader (EA11 or EA21), GPS, Serial Dongle, Ethernet, MicroSDXC or second USB 2.0 port³
- Choice of bridge battery, magstripe reader, insertable SmartCard reader, insertable SmartCard reader with bridge battery, contactless SmartCard/RFID HF reader or UHF 900MHz RFID reader (EPC Gen 2)¹⁷

ACCESSORIES¹⁰

- | | |
|--|--------------------|
| ■ AC Adapter (3-prong) | CF-AA6413CM |
| ■ Standard Battery Pack | FZ-VZSU84U |
| ■ Long Life Battery Pack ⁷ | FZ-VZSU88U |
| ■ Long Life Battery Bundle | |
| (includes rotating hand strap and corner guard set) | FZ-BNDLG1LL1ST1CG4 |
| ■ Single Battery Charger Bundle | FZ-BNDLG1BATCHRG |
| ■ LIND 3-Bay Battery Charger | FZ-BND3BAYG1 |
| ■ LIND Car Adapter 120W | CF-LNDDC120 |
| ■ LIND Car/AC Adapter 90W (with USB port) | CF-LNDACDC90 |
| ■ LIND Car Adapter 90W MIL-STD | CF-LNDMLDC90 |
| ■ Tall Corner Guard Set | FZ-VEBG11AU |
| ■ Rotating Hand Strap and Tall Corner Guard Set Bundle | FZ-BNDLG1ST1CG4 |
| ■ ToughMate G1 Always-On Case (with hand strap) | TBCG1A0NL-P |
| ■ ToughMate G1 Professional Portfolio | TBCG1PFLIO-BLK-P |
| ■ ToughMate G1 "X" Hand Strap | TBCG1XSTP-P |
| ■ Desktop Cradle | FZ-VEBG11AU |
| ■ Vehicle Docks (no pass-through) | |
| – Gamber-Johnson | 7160-0486-00-P |
| – Havis with LIND power supply | CF-H-PAN-702-P |
| ■ Vehicle Docks (dual pass-through) | |
| – Gamber-Johnson | 7160-0486-02-P |
| – Havis with LIND power supply | CF-H-PAN-702-2-P |
| ■ Cradlepoint Router | |
| – Verizon | CP-IBR1100LPE-VZ |
| – AT&T | CP-IBR1100LPE-AT |
| ■ Replacement Digitizer Pen Waterproof | FZ-VNPG11U-S |
| ■ Tether | FZ-VNTG11U |
| ■ 10.1" LCD Protective Film | FZ-VPFG11U |

Please consult your reseller or Panasonic representative before purchasing.

Caution: Do not expose bare skin to this product when handling this unit in extreme hot or cold environments.

¹ Approximate time. Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other customer preferences. Battery testing results from MobileMark 2007.

² Bridge battery, magstripe reader, insertable SmartCard reader, insertable SmartCard reader with bridge battery, contactless SmartCard reader and UHF RFID reader are mutually exclusive. Please note, USB 3.0 port cannot be accessed when the unit is equipped with the magstripe reader, but optional USB 2.0 port can be accessed.

³ GPS, Serial Dongle, Ethernet, MicroSDXC and second USB port are mutually exclusive options.

⁴ 1GB = 1,000,000,000 bytes.

⁵ Total usable memory will be less depending upon actual system configuration.

⁶ The size of the VRAM cannot be set by the user and varies by operating system as well as the size of the RAM. Windows 7 max. VRAM is 1555MB.

⁷ Magstripe reader, insertable SmartCard reader, insertable SmartCard reader with bridge battery and UHF RFID reader include tall corner guards and rotating hand strap. Bridge battery (without SmartCard reader) includes medium corner guards and rotating hand strap.

⁸ Requires software and activation to enable theft protection.

⁹ Length measurements do not include protrusions. Weight varies with options and digitizer pen.

¹⁰ Accessories and Integrated Options may vary depending on your configuration. Visit the Panasonic website for more accessories and details.

¹¹ Hazardous location certifications may not apply to all configurations. Consult your Panasonic representative for availability.

¹² TPM 2.0 available upon request - please contact your reseller or Panasonic representative.



1.800.662.3537

panasonic.com/toughpad/G1

Panasonic is constantly enhancing product specifications and accessories. Specifications subject to change without notice. Trademarks are property of their respective owners. ©2016 Panasonic Corporation of North America. All rights reserved. Toughpad FZ-G1 mk3 Spec Sheet_10/16

TOUGHPAD