



Silicone Wristband Tag

FEATURES


- The silicone wristband passive RFiD Tag with high capacity multi read/write capability in Wrist watch shape and is elegant in look. Reads up to 3-4 meters!!
- The tag is flexible, hence it can be fitted in different sizes of wrists.
- Dust & water proof
- Soft and non allergic to skin

APPLICATIONS

- Access Control and Security in various places like Amusement park, Clubs, Theaters etc.
- Keyless Hotel Room and Locker Entry
- Prevention of Counterfeitation.
- Hospital and event management
- Customer Loyalty Programs

Chip Type:	Alleri riiggs 3 Ei 6 6lass 1 6cli 2	
	EPC 96 bit extendable upto 480 bits	
	User Memory 512 bit	
	Data retention of 50 years	
	Write endurance 100.000 cycles	
Mechanical:	Strap Dia.	65 mm
	Width	28 mm
	Thickness	11.50 mm
	Material	Silicon Rubber
	Weight	20 gm
Electrical:	Operating Frequency	865-868MHz, (902-928MHz also available on request)
Licoti icai.	Operating mode	Passive (battery-less transponder)
Ingress Protection:	IP67	
Thermal:	Storage Temp.	-25°C to +85°C
The mai.	Operating Temp.	-25°C to +85°C
Part Number:	393V1	
0-1	Available with:	
Options:	Other IC type on request	

Alien Higgs 3 EPC Class 1 Gen 2



Tag Placement

♣ To get best performance it is strictly recommended to use circular polarized antenna.

