

TMX2200

ThermaMAX Thermal
Transfer Ribbon



- Automotive components
- Medical specimens (vials, slides, etc.)
- Lawn and garden equipment
- Building products
- Oil and gas industries
- Valuable asset tracking
- Industrial bins
- Transportation and logistics
- Compliance labeling
- Lumber tracking
- Horticultural

Mid-Range ThermaMAX Thermal Transfer Ribbon

Intermec's ThermaMAX TMX2200 ribbon, when paired with compatible labels, and tags, provides high image quality and enhanced abrasion/smear resistance. TMX2200 is engineered to print on a wide range of materials, both papers and films. The ThermaMAX TMX2200 ribbon is ideally suited for materials such as:

- Duratran II Paper Label
- Duratran II Paper Tag
- Duratran II Syntran
- Duratran II Kimdura Label
- Duratran II Synthetic Tag
- Duratran II Valeron Tag

Better Together

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting
- When Intermec media is used exclusively with Intermec printers, the Free Printhead Replacement Program offers significant cost savings

Product Characteristics:

Ribbon Construction

Total Ribbon Thickness: < 9 µm

Ribbon Film Thickness: 4.4 to 5.2 µm

Ribbon Film Type: Polyethylene terephthalate

Properties

Ink color: Black

Ink Pigment: Carbon black

Image Density (4ips/4420): 1.8 OD min.

Flaking Resistance: No flaking

Film Break Strength (MD): 300N/mm min.

Film Shrinkage: 3% max. at 150° C/30 min.

Performance Attributes

Scratch (2ips/Kimdura): C at 50 cycles/2.95# arm

Ambient Operating Temperature and

RH: 5 to 35°C, 5 to 70% RH

Print Quality (4ips/PM4i): ANSI A on 10mil ladder

Printers

Intermec labels and tags are engineered to produce optimum print quality when used in Intermec printers with the proper ribbon/material combination.

Storage Conditions

Temperature: 41°F to 95°F OR 5°C to 35°C

Relative Humidity: 20 to 85% RH

Shelf Life: 12 months

North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

Intermec Deutschland

Burgunder Strasse 31
40549 Düsseldorf
Germany
Phone: 0049 211 53601-0
Fax: 0049 211 53601-50
Email: germany.marketing@intermec.com
Web: www.intermec.de

South America & Mexico

Headquarters Office

Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611841-A 09/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

