

REA VERIFIER

QUALITY CONTROL DEVICES
FOR MATRIX- AND BARCODES

REA Check ER

Small, powerful, portable Verifier
for printed barcodes



REA Check ER

The start of portable bar code verification



The REA Check ER is a portable, battery powered bar code Verifier. Its manufacture in conformity with international standards in Germany.

The REA Check ER has the following unique features:

- Compact design
- Built-in battery for portable operation
- Cable free in portable operation
- Large colour display
- Built in memory for up to 1000 reports
- USB interface to connect portable printer
- Reliable Ethernet communication for PC interface
- DHCP automatic network configuration

The REA Check ER is a combination of a very small device which includes the powerful and comfort features of the REA VERIFIER product line. The small size and solid State construction makes this device a perfect tool for portable bar code verification.

The final result Pass or Fail is the central part of the Verification report. The still quick available details allow a fast deeper analysis.

Optional hardware accessory:

Report printer REA TD-GPT-U

The printer is connected with an USB cable to the REA Check ER. The printout is a 57 mm wide paper strip. The printer has a built in battery pack to allow a fully portable operation including report print locally on demand.

Software options:

REA TransWin 32


Manages report view, saving, export and printing. Additionally REA TransWin 32 can remote control and configure REA Verifiers. Report Print outs are done on standard office printers (local or network). Via a PDF writer REA TransWin 32 creates report in PDF file format. REA TransWin 32 requires a Windows PC for operation.

Optional Symbologies

An additional set of optional bar code symbologies. These symbologies are in use in pharmaindustry, healthcare, postal services and other applications.

Code Compare

This function compares the actually decoded bar code content with a previously stored master code. Equal code contents are accepted. All other combination will cause a failed result. The user can select if the result shall be graded or if the result is shown only informative.



Verifier



REA Check ER

REA Article Database 32

This is a database which assigns to each verified barcode additional article informations. This is i. e. the article description, a price secondary article informations and date informations. Date informations like „best before use“ or „Use until“ can verified individually for each article and lead separate to a pass/fail result if dates in the code are incorrect. In principle Article Database 32 can be configured by the user to provide a fail result if the article does not exist and/or if the date range is incorrect. This additional data base supported code content control replaces a separate control step for this requirement.

Verification/evaluation of the following code types possible:

EAN-13, UPC-A, UPC-E without/with Add-On, EAN-8, 2/5 Interleaved with/without check digit, ITF-14, freight mail, Code 39 with/without check digit, PZN code, code 32, Code 128, GS1-128 with/without content check, GS1 Databar

Optional code type extension:

2/5 3 bars, 2/5 5 Bars, 2/5 IATA, 2/5 Baggage, 2/5 DHL Express (cargo mail code), Code39 Full ASCII, Code 93, MSI, Plessey, code 128 UPU, code 39 UPU, Code 39 HIBC, Code 128 HIBC, Codabar Monarch (18), LAETUS Pharmacode, LAETUS Mini Pharmacode

Code Types:

- **Barcodes (1D):**
EAN-13, UPC-A, UPC-E with/without ADD-ON, EAN-8, 2/5 Interleaved with/without check digit, ITF-14 (Freight code), Code 39 with/without check digit, PZN-Code, Code 32, Code 128, GS1-128 with/without content verification, GS1 Databar (limited, stacked, expanded, expanded stacked, truncated, omnidirectional), GS1 Databar composite
- **Optional Codes (1D):**
2/5 3 Bars, 2/5 5 Bars, 2/5 IATA, 2/5 Baggage, 2/5 DHL Express (Freight code), Code39 Full ASCII, Code93, MSI, Plessey, Code 128 UPU, Code 39 UPU, Code 39 HIBC, Code 128 HIBC, Codabar Monarch (18), LAETUS Pharmacode, LAETUS Mini Pharma Code

Features:

- Bar code verification according to ISO/IEC 15416 or ANSI X3.182
- Simple configuration for different demands like incoming goods control or print process control
- Saving of complete configuration as settings profile
- Setting profiles can be exported and imported. This allows to share settings and save them on a PC.
- Pass/fail setting for grade preset A/4, B3, C/2 or D/1
- Automatic averaging of scans starting with 2 and up to 10 scans
- Auto discrimination of all major bar code symbologies
- Automatic size and check digit control
- Light margin inspection in extended areas
- Ratio verification for two bar width symbologies like Code 39 and 2/5 interleaved
- Verification according GS1 General Specifications for retail codes
- Included GS1-128 Data structure verification for GS1-128 and GS1-Databar codes
- Colored LED's for quick pass/fail indication and operation status
- Multi language user interface and verification reports
- Simple software update via network or USB Memory stick
- PC operation does not require driver installations

Technical Data:

- Measuring accuracy in conformance with ISO/IEC 15426-1
- ARM9, 32 bit microprocessor, 180 Mhz, 32 MB RAM, 32 MB Flash ROM, 512 MB MMC flash memory
- Operating System: Embedded Linux
- LED red light illumination, 660 nm, 45°
- Measuring width 75 mm (including light margins)
- Aperture: 6, 8 and 10 mil ((this is 0,15, 0,2 or 0,25 mm)
- Metric measuring accuracy: +/-5 % for average bar deviation, +/-10 % for extreme bar deviation; contrast accuracy: +/-8 %
- Interfaces:
 - RJ45 Ethernet socket for network or PC connection (standard TCP/IP)
 - USB 2.0 socket for portable printer connection and for software updates
- Large color display and 12 keys for direct local operation and graphical report visualisation
- Power supply: Built-in LithiumIon battery pack and over „Power Over Ethernet“ power supply (100 to 240 Volt, 50/60 Hz, C13 socket for standard power cords (UK, US, EUR), two Ethernet CAT5 flexible patch cables included.
- Size (L x B x H): 222 x 85 x 95 mm
- Weight: 660 g
- System Requirement: PC with Windows 7, 64 bit or later



Portable report printer



Local verification

Symbol	Pass 3.0/10/670			
SRP Grade	3.0			
Selected Grade	2 (1.5)			
Symbology	UPC-A			
Code content	013800103215			
ISO/IEC 15416	ISO/IEC 15420			
0	1	2	3	4
Decode				3
Symbol Contrast	88%	min 40%		4
Edge Contrast	63%	min 15%		4
Modulation	72%	min 50%		4
Rmin/Rmax	4%	max 50%		3
Defects	12%	max 25%		4
Decodability	52%	min 37%		3

REA VERIFIER



REA Elektronik GmbH

Teichwiesenstrasse 1

64367 Muehltal

Germany

T: +49 (0)6154 638-0

F: +49 (0)6154 638-195

E: info@rea-verifier.de

www.rea-verifier.com