

HONEYWELL GRANIT XP ACCESSORIES GUIDE

Honeywell

STANDS, HOLDERS, CORDLESS BASES, AND ACCESS POINTS



HOLDER-010-U

Wall-Mount Cup

Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



STND-30R00-011-4

Rigid Presentation Stand

Stand: gray, 5" rigid rod, weighted base, Granit cradle.



STND-33F00-012-4

Flexible Presentation Stand

Stand: gray, 9" flexible rod, weighted base, Granit cradle.



VMHOLDER

Vehicle mount holder

Vehicle mount kit contains vehicle mount forked holder, adjustable arm with ball joints, and mounting hardware



AP-05-100BT-07N

Bluetooth Access Point

Access point for Granit XP and Granit 1981i scanners. Class 1 Bluetooth, 100m, up to 3 Granit XP scanners can be connected (cables sold separately).



AP-100BT-07N

Bluetooth Access Point

Access point for Granit XP scanners. Class 1 Bluetooth, 100m, up to 3 Granit XP scanners can be connected (cables sold separately).



TOOLBAL

Take-Up Reel/Tool Balancer

Suspension reel commonly used for scanner mounting/retention on vehicles and in fixed locations.

CHARGE AND COMMUNICATIONBASES, CHARGERS AND BATTERIES

				
BAT-SCN05	CCB22-100BT-03N	COB22	MB4-BAT-SCN01NADO	MB4-BAT-SCN01NAWO
Smart Battery Pack Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.	Granit XP Charge/Communication Base Base: Charge and communication. Class 1 Bluetooth. 100m (300'), up to 3 scanners can be connected. Compatible with RS232/USB/KBW cables (sold separately).	Granit XP Charge Only Base Base: Charge only. Only one scanner can be connected at a time. Power supply required and must be purchased separately.	4-Bay Battery Charger - Desk Mount 4-bay battery charger (NA) for use with Granit and Xenon Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).	4-Bay Battery Charger - Wall Mount 4-bay battery charger (NA) for use with Granit and Xenon lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

HEATERS

				
520L-12-S3	520L-24-S3	520L-3648-S3	521L-12-S3	521L-3648-S3
Scanner Heater with Cable Retractor 12V heater for Granit scanners in freezer environments	Scanner Heater with Cable Retractor 24V heater for Granit scanners in freezer environments	Scanner Heater with Cable Retractor 36-48V heater for Granit scanners in freezer environments	Scanner Heater 12V heater for Granit scanners in freezer environments	Scanner Heater 36-48V heater for Granit scanners in freezer environments

CABLES AND POWER SUPPLIES

CBL-020-300-C00	CBL-020-300-C00-01	CBL-020-300-C00-02	CBL-020-500-C00	CBL-1020-300-C00
RS-232 Power Cable Cable: RS-232(5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	RS-232 Power Cable Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	RS-232 Power Cable Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	RS-232 Power Cable Cable: RS-232(+5V signals), black, DB9 female, 5 m (16 ft), coiled, external power with option for host power on pin 9.	RS-232 Power Cable Cable: RS-232 (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9.
CBL-220-300-C00	CBL-320-300-C00	CBL-500-300-C00	CBL-500-300-S00	CBL-500-300-S00-01
RS-232 Power Cable Cable: RS-232 (5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9.	RS-232 Power Cable Cable: RS-232 (+/- 12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9.	USB Power Cable Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power.	USB Power Cable Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power.	USB Power Cable Cable, Industrial (for freezer environments) USB, black, Type A, 3m (9.8'), straight, 5V host power.
CBL-500-500-C00	CBL-501-300-S00	CBL-503-300-C00	CBL-503-300-S00	CBL-503-500-C00
USB Power Cable Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power.	USB Power Cable Cable: USB Granit scanner cable, compatible with USB D9 connectors on VM series docks.	USB Power Cable Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power.	USB Power Cable Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power.	USB Power Cable Cable, USB, black, 12V locking, 5m (16.4'), coiled, 5V host power.
CBL-720-300-C00	CBL-720-370-C00	MX009-3MA8SN	46-00525-6	46-00526
KBW Power Cable Cable: KBS, black, PS2, 3m (9.8'), coiled, 5V external power with options for host power.	PS-2 Power Cable Cable: PS-2 Keyboard Wedge, Coiled, 5V.	USB Power Cable Cable: USB POS, Type A, Straight, Black, No PowerL	Power Supply – NAPlug Power Supply: NA plug, 10A@ 5.2VDC, 90-255V AC @ 50-60 Hz.	Power Supply – EUPlug Power Supply: EU plug, 10A@ 5.2VDC, 90-255V AC @ 50-60 Hz.
46-00528	46-00529			
Power Supply – AUPlug Power Supply: AU plug, 10A@ 5.2VDC, 90-255V AC @ 50-60 Hz.	Power Supply – CNPlug Power Supply: CN plug, 10A@ 5.2VDC, 90-255V AC @ 50-60 Hz.			

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com