

















C71

Mobile Computer

- | | | | | | | |
|--|--|--|--|---|---|--|
| 
Android | 
4G | 
WiFi | 
Bluetooth | 
1D Barcode | 
2D Barcode | 
Fingerprint |
| 
PSAM | 
UHF | 
Infrared | 
IRIS | 
NFC/HF | 
Camera | 
GPS |

Chainway C71 with abundant functions is an Android rugged mobile computer. With its powerful processor, stable wireless connections and comprehensive data capture options, you can find this easy-to-deploy device a valuable helper to increase productivity in logistics, warehousing, retail, identity verification, meter reading, IC card reading and etc.



Specification

Performance	
CPU	Cortex-A53 Octa-core 2.5 GHz
RAM+ROM	3 GB + 32 GB / 4 GB + 64 GB
Expansion	Supports up to 128 GB Micro SD card
Operating System	Android 8.1; Soti MobiControl, SafeUEM supported

Communication	
WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
WWAN (China)	2G: 900/1800 MHz
	3G: WCDMA: B1/B8
	CDMA2000 EVDO: BC0
WWAN (Europe)	TD-SCDMA: B34/B39
	4G: B1/B3/B5/B8/B34/B38/B39/B40/B41
	2G: 850/900/1800/1900 MHz
WWAN(America)	3G: B1/B2/B4/B5/B8
	4G: B1/B3/B5/B7/B8/B20/B40
	2G: 850/900/1800/1900 MHz
WWAN(Other)	3G: B1/B2/B4/B5/B8
	4G: B2/B4/B7/B12/B17/B25/B66
Bluetooth	Depending on the country's ISP
Bluetooth	Bluetooth v2.1+EDR,3.0+HS,v4.1+HS
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Physical Characteristics	
Dimensions	164.2 x 78.8 x 17.0 mm / 6.46 x 3.1 x 0.67 in. (for standard version)
Weight	<288 g / 10.15 oz. (for standard version)
Display	5.2" IPS FHD 1920x1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, built-in 5000 mAh
	Standby: over 350 hours
	Continuous use: over 12 hours (depending on user environment)
	Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB 2.0 Type-C, OTG, TypeC headphones supported
Audio	Speaker, 2 microphones
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
Sensors	Gravity sensor, light sensor, proximity sensor, vibration motor

Developing Environment	
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment	
Operating Temp.	-4 °F to 122 °F / -20 °C to 50 °C
Storage Temp.	-40 °F to 158 °F / -40 °C to 70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.8 m / 5.9 ft. drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature

Sealing	IP65 / IP67 per IEC sealing specifications
ESD	±15 KV air discharge, ±6 KV conductive discharge

Data Collection

Camera

Rear Camera	13 MP Autofocus with flash
-------------	----------------------------

Front Camera (optional)	5 MP camera
-------------------------	-------------

Barcode Scanning (optional)

1D Linear Scanner	Zebra: SE965; Honeywell: N4313
-------------------	--------------------------------

1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
----------------	--

2D Imager Scanner	Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603
-------------------	---

2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.
----------------	---

Iris (optional)

Rate	< 150 ms
------	----------

Range	20-40 cm
-------	----------

FAR	1/10000000
-----	------------

Protocol	ISO/IEC 19794-6, GB/T 20979-2007
----------	----------------------------------

*Iris is alternative to front camera.

HF (optional)

Frequency	13.56 MHz
-----------	-----------

Protocol	ISO14443A/B, ISO15693
----------	-----------------------

Chips	M1 card (S50/S70), M0 (Ultralight), M3 (Desfire D40/D41/D81), CPU_A card, CPU_B card, ICODE II, TI2048, LRI64K, Others for customization
-------	--

Range	3-8 cm
-------	--------

NFC (optional)

Frequency	13.56 MHz
-----------	-----------

Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
----------	---

Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
-------	--

Range	2-4 cm
-------	--------

UHF (optional)

Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
-----------	---

* For detailed specification, please check C71 UHF data sheet

InfraRed (optional)

Frequency	38 kHz
-----------	--------

* For detailed specification, please check C71 InfraRed data sheet

Fingerprint (optional)

Sensor	Capacitive TCS1 / TCS2; Optical Morpho CBM-E3
--------	---

* For detailed specification, please check C71 Fingerprint data sheet

PSAM (optional)

Card slot	2 slots for PSAM cards
-----------	------------------------

Protocol	ISO7816 T=0, T=1
----------	------------------

Accessories

Standard	AC Adaptor, USB Cable, Lanyard, etc.
----------	--------------------------------------

Optional	Cradle, Holster, etc.
----------	-----------------------

* For detailed specification, please check Accessory Guide.

Notice: Product specifications are subject to change without prior notice. / Model: C71 / Update Date: 2020-07-14

CHAINWAY[®]

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net