


DATASHEET EOS-100

EOS-100

The Tageos EOS-100 is a wide-band Gen2 UHF RFID label with a short read range designed for Jewelry tagging. The label is die-cut to provide three different label shapes suitable for tagging earrings, rings, necklaces and watches.





GENERAL SPECIFICATIONS

LABEL CONFIGURATIONS

FCC 902–928 MHz / ETSI 865–868 MHz / ASIA 950–956 MHz

Protocol EPC Class 1 Gen 2

EPC memory Up to 128 bits

User memory Up to 128 bits

Antenna size 14 x 11 mm / 0.55 x 0.43 in

100 X 26 mm / 3.94 X 1.02 in






MECHANICAL **DIMENSIONS**

Label size

DIMENSIONS	DESCRIPTION	METRIC	US
AxB	Antenna size	14 X 11 MM	o.55 x o.43 in
CxD	Die-cut size	100 X 26 MM	3.94 X 1.02 in
Е	Web width	106 mm	4.17 in
F	Pitch	30 mm ± 0,5 mm	1.18 in
G	Die-cut to web edge	3 mm	0.12 in
HxI	Label size	96 x 24 mm	3.78 x 0.94 in
К	Bad mark	Ø 4 mm	Ø 0.62 in



FEED DIRECTION



DATASHEET EOS-100

RFID CHIP SILICON

TAG SILICON	ALIEN HIGGS 4	IMPINJ MONZA R6	IMPINJ MONZA R6-P
Protocol	EPC Class 1 Gen 2	EPC Class 1 Gen 2	EPC Class 1 Gen 2
Operating frequency	860 – 960 MHz	860 - 960 MHz	860 - 960 MHz
EPC memory	Up to 128 bits	96 bits	Up to 128 bits
User memory	128 bits	-	Up to 64 bits
Operating temperature	-50°C / +85°C (-58°F / +185°F)	-40°C / +85°C (-40°F / +185°F)	-40°C / +85°C (-40°F / +185°F)

PRODUCT CHARACTERISTICS

	ADHESIVE LABEL
Antenna material	Aluminum
Front face material	Glossy white TT printable coated paper
Back face material	-
Adhesive	Solvent-free permanent acrylic adhesive
Final inspection	100% tested, defective tags marked

DELIVERY **CONDITIONS**

	ADHESIVE LABEL
Packaging	Roll (single row)
Core inner diameter	76 mm / 3 in
Roll outer diameter	200 mm / 7.87 in
Unwinding direction	Labels on inside of roll
Standard roll size	2500 pcs
Minimum order quantity	One roll

CERTIFICATIONS & APPROVALS



CONTACT
CONTACT@TAGEOS.COM
WWW.TAGEOS.COM

TAGEOS HEADQUARTERS 515, RUE ALFRED NOBEL 34000 MONTPELLIER TAGEOS NORTH AMERICA 609 SW 8TH STREET, SUITE 600 BENTONVILLE, AR 72712 USA

STORAGE & HANDLING PRECAUTIONS: Observe standard storage and handling practices to minimize Electro Static Discharge. Tageos reserves the right to change its products and services at any time without notice. As our products are used in circumstances beyond our control, we cannot be held liable for any damages caused through their use.

This is a general purpose product not designed or intended for any specific application. The pictures and illustrations found on this document are for illustration purposes only, and do not necessarily represent the exact products. Tageos is a registered trademark. All other trademarks are the property of their respective owners.