
# Urovo

# DT50P Lite

# Lightweight UHF RFID Handheld Reader



Weighing just 498g, the device's ergonomic design ensures effortless handling allowing for extended usage without compromising on comfort.

# **Unmatched RFID Performance, Exceptional Efficiency**

Powered by the Impinj E710 chip and supporting Impinj Gen2X, it delivers an RFID reading rate of 1300+ tags per second and a range of over 15 meters, significantly enhancing work efficiency.

### **Powerful Performance, Effortless Multitasking**

Equipped with a Qualcomm Octa-core 2.45 GHz processor and Android 13.0, it ensures fast response times and seamless multitasking for high-performance applications.

#### **Fast and Stable Data Transmission**

Supports Wi-Fi 6 Ready, 2.4 GHz and 5 GHz dual-band Wi-Fi, and 4G network, providing fast and stable data transmission indoors and outdoors.

#### **Endurance You Can Count On**

Equipped with a 6500mAh removable battery, providing reliable power for your all-day workload and ensuring uninterrupted productivity.







# DT50P Lite Lightweight UHF RFID Handheld Reader



# **Specifications**



Octa-core 2.45 GHz



O.S.

Android 13



#### Memory

RAM: 4GB ROM: 64GB Micro SD, up to 256GB



### □ Display

5.7 inch display (720×1440)



Ultra sensitive capacitive touch panel

Supports multi-touch Works with gloves, wet fingers

#### **Dimensions**

Size: 132 x 162.6 x 78mm Weight: 498g



Microphone (noise cancellation); Speaker (1.3W) Receiver

# **Scanning**

Professional scan engine Supports international standard 1D/2D barcodes Support barcode displayed on screen and colored barcode



3.85V / 6500mAh

#### Camera

Front 5MP Top 13MP with flash

#### **Buttons**

PWR button Vol+/- button Scan button \* 2 Custom button \* 1

#### Card slot

Micro SD \* 1 Nano-SIM \* 2

### ((•)) RFID(UHF)

Reading Range: 15m+ Read Rate: 1300+ tags/sec (\*Environment-Based; Data from UROVO Lab)

### Communication

4G. 3G. 2G BT5.0 + BR/EDR + BLE 2.4G/5G. IEEE 802.11 a/b/g/n/ac/d/e/h/i/k/r/v/w/ax ready

# Positioning

GPS、A-GPS、BeiDou、 GLONASS Galileo

#### **Protection**

IP67 dustproof and waterproof 1.5-meter drop resistance

#### **®** Environment

Operating temperature: -20 ~ +60°C Storage temperature: -40 ~ +70°C Humidity: 5%RH ~ 95%RH (non-condensing) ESD: +/-15kv Air; +/-8kv contact

#### **UROVO PTE. LIMITED**

Website: en.urovo.com Email: urovo@urovo.com Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1, Singapore 048616

#### **Urovo Europe**

Website: europe.urovo.com Email: sales-europe@urovo-emea.com Address: de Maas 9, 5684PL. Best, the Netherlands

#### **Urovo North America**

Website: us.urovo.com Email: urovo@urovo.com

Address: 1990 Main Street, Suite 750, Sarasota,

Florida 34236

\*This page is subject to change without prior notice