




VERSA TRAK

Technical Specifications

- **RF protocol** EPC global Class 1 Gen2
- **Frequency** 860-960 MHz (Global)
- **IC type (chip)**¹ Impinj M750
- **Chip memory** 96 bits EPC; 96 bits TID; 32 bits user memory
- **Read range** On metal² Up to 29.5 ft (9 m)
- **Read range** Off metal² Up to 9.8 ft (3 m)
- **Polarization** Linear
- **Radiation Pattern**



Key features

- + **Multi-Surface on/off metal**
- + **Superior read range:** up to 9m
- + **High performance yet cost-effective**
- + **Various and easy mounting systems**

Applications

- **Returnable Transport Item (RTI) Management**
- **Pallet Logistics**
- **Storage Rack Identification**

Environmental Specifications

Temperature



- **Operational temperature** -40°C to +85°C
- **Survival temperature** -40°C to +85°C


- **IP rating** IP68
- **Compression strength** 26.1 psi (180 kPa)
- **Shock (drop)** 3ft (1 m) to concrete/granite
- **Vibration** MIL-STD-810G
- **Warranty** 1 year

¹ The chip data retention is up to 50 years, based on chip operating under general environment conditions.

² Fix reader

Physical Specifications

- **Material** Industry grade polymer
- **Dimensions (in)**¹ 1.98 x 0.67 x 0.21
- **Dimensions (mm)**¹ 50.30 x 17 x 5.30
- **Weight** 0.11 oz (3 g)



Mounting Systems

- High performance adhesive
- Cable tie (optional)

Installation Instructions

Instructions for optimal performances:

1. Clean the surface using Isopropyl alcohol, alcohol pad or equivalent solvent to ensure surface is free from dirt, dust, oil and misc,debris that may affect adhesion.
2. Handle the tag by edges, peel release liner from back ensuring not to touch the adhesive.
3. Place the tag in desired tagging location and firmly apply even pressure to the tag for 5 seconds.
4. Do not disturb newly mounted tag for at least 15 minutes to ensure proper adhesive seating.

¹ Tolerance: +/- 0.02; +/- 0.5

Industry Compliance



Order Information

Versa Trak Global: X0350-GL011-M750

Customization Options

Encoding

ATEX Certified Version

Printing

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet..

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.