




## SLIM TRAK

### Technical Specifications

- **RF protocol** EPC global Class 1 Gen2
- **Frequency** 860-960(Global)
- **IC type (chip)**<sup>1</sup> Alien Higgs 9
- **Chip memory** 96 bits EPC; 48 bits TID; 688 bits User Memory
- **Read range** Off metal<sup>2</sup> Up to 3.3 ft (1 m)
- **Read range** On metal<sup>2</sup> Up to 6.5 ft (2 m)
- **Polarization** Linear
- **Radiation Pattern**



### Key features

- + **Slim profile:** designed for small assets
- + **Global frequency:** Worldwide Compatibility
- + **Withstand high temperature:** up to 150°C
- + **Cost effective**

### Applications

- MRO Tool Tracking
- IT Asset Management
- Military Asset & weapon Tracking

### Environmental Specifications

**Temperature**

- Operational temperature -40°C to +85°C
- Survival temperature -40°C to +150°C


- **IP rating** IP68
- **Compression strength** 14.5 psi (100 kPa)
- **Impact** 3ft (1 m) to concrete/granite
- **Vibration** MIL-STD-810G
- **Warranty** 1 year

<sup>1</sup> The chip data retention is up to 50 years, based on chip operating under general environment conditions.

<sup>2</sup> Fix reader

## Physical Specifications

- **Material** RF4
- **Dimensions (in)**<sup>1</sup> 2.22 x 0.234 x 0.0512
- **Dimensions (mm)**<sup>1</sup> 56.5 x 5.95 x 1.3
- **Weight** 0.035 oz (1 g)



## Mounting Systems

- High Performance Adhesive

## Installation Instructions

Instructions for optimal performances:

1. Clean the surface using Isopropyl alcohol, alcohol pad or equivalent solvent to ensure surface is free from dirt, dust, oil and misc, debris that may affect adhesion.
2. Handle the tag by edges, peel release liner from back ensuring not to touch the adhesive.
3. Place the tag in desired tagging location and firmly apply even pressure to the tag for 5 seconds.
4. Do not disturb newly mounted tag for at least 15 minutes to ensure proper adhesive seating.



<sup>1</sup> Tolerance: +/- 0.01; +/- 0.15

## Industry Compliance



## Order Information

Slim Trak: X0330-GL001-H9

## Customization Options

Encoding

ATEX Certified Version

Silk Screen

The information provided by Xerafy Singapore Pte. Ltd. is for general information purposes only. All information on the datasheet is provided in good faith. However we make no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, validity, reliability, availability, or completeness of any information on the datasheet..

Under no circumstance shall we have any liability to you for any loss or damage of any kind incurred as a result of the use of the product or reliance on any information provided on the datasheet. Your use of the product and your reliance on any information on the datasheet is solely at your own risk.