

PRESENTATION SCANNERS

Magellan™
Magellan™

900i
1500i





FOCUS ON MAGELLAN 900i & 1500i

PRESENTATION SCANNERS

The Magellan 900i is best suited for general purpose scanning and SCO/kiosk applications.
The Magellan 1500i is best suited for applications where high-performance scanning or an ultra compact, stylish design is required.



PRESENTATION SCANNER OFFER

MAGELLAN 900i



Superior Scanning Performance — delivers up to 30% faster reading speeds* with seamless scanning from both printed and mobile sources.

* than the previous generation model GPS44XX



Adaptive Illumination & Visual Feedback — Optimizes lighting to ensure reliable reading of all barcode types with Green Spot for positive scan feedback.



Easy to use: Comfortable, ergonomic design to easy installation and to adapt to any application.

Stylish design in black or white with a premium aluminium base, it fits seamlessly on any counter or kiosk —ready for any retail setup.



Kiosk bracket and compact size allow for simple OEM integration in self-checkout kiosks.



Smarter scanning with a built-in **accelerometer** for an easy and ergonomic transition to handheld scanning.



MAGELLAN 1500i



READY FOR THE FUTURE:

Magellan 900i and Magellan 1500i are ready to scan OCR and **GS1 Digital Link barcodes**.



GS1 Digital Link Ready

READY FOR THE FUTURE:
Magellan 900i and Magellan 1500i are ready for GS1 Digital Link.



- Enables access to dynamic product data, promotions, traceability, and digital experiences — all from a single scan.
- Supports omnichannel workflows, from in-store engagement to post-sale information.
- Future-proofs your checkout for upcoming GS1 and regulatory standards.



EXPIRATION DATE



DISCOUNTS




NUTRITIONAL VALUES



INGREDIENT TRACEABILITY



PLANT PRODUCTION & SUPPLY
CHAIN DATA



LOT NUMBER

THE NEXT RETAIL REVOLUTION:

By 2027 many packages will include 2D GS1 Digital Link code alongside the 1D code; GS1 can be formatted as a QR code or Datamatrix and is able to store more information. Digital content can be continuously updated by a brand owner, without changing the GS1 Digital Link code on the packaging.



Magellan 900i white model



NEW MAGELLAN 900i WHITE MODEL: TECHNOLOGY MEETS DESIGN

The Magellan™ 900i is now available in two color options—classic black and the new refined white plastic. The white version is designed for environments where a lighter, cleaner aesthetic is preferred, such as modern and minimal white counters or healthcare settings. While the exterior color changes, the internal technology and software remain exactly the same, ensuring consistent performance across both models. This new option enhances visual versatility, offering customers the freedom to choose the design that best fits their space — where quality meets design.



Presentation Scanners applications



 ACCESS CONTROL



TICKETS & IDENTITY DOCUMENTS CONTROL 



 HEALTHCARE - LABORATORY



SELF-SERVICE/SELF-CHECKOUT 



 POS CHECKOUT




PHARMA CHECKOUT 

Service programs

Datalogic's EASEOFCARE Service Programs provide superior life-cycle support to ensure that products are always operating at peak performance.

Our market-leading Care programs are a key reason for customers to choose and keep Datalogic products, maximizing their uptime and lifecycle so that they can also be assured that their software is always running on a healthy and reliable device.



FAST REPAIR TURNAROUND
(OVERNIGHT / 2 DAYS / 3 DAYS / 5 DAYS)



ACCIDENTAL DAMAGE COVERED BY COMPREHENSIVE PACKAGE (OR OPTION)



BOTH WAYS FREIGHT PAID BY DATALOGIC*



3-5 YEARS CONTRACT SERVICE OPTIONS

** on overnight/2days only*

Technical specifications

MAGELLAN 900i



INDUSTRY - APPLICATION

Retail:

- Point-of-Sale
- Mobile Marketing
- Age Verification
- 2D bar codes

Commercial Services:

- Postal
- Banks
- Public Administration
- Utilities

Healthcare:

- Patient Bedside Care
- Laboratory
- Pharmacy
- Admittance, Accounting and Billing

OEM:

- Self Checkout
- Customer Service Kiosk
- Price Verification
- Boarding Pass
- Access Control
- Admission Turnstiles
- Parking Machines

DECODING CAPABILITY	
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code, Data Matrix, MaxiCode, QR Code
Postal Codes	Australian Post; British Post; Canadian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post
Stacked Codes	GS1 DataBar Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; Micro PDF417, PDF417
ELECTRICAL	
Current	Operating (Typical): < 300 mA Standby/Idle (Typical): < 175 mA
Input Voltage	5 VDC +/- 10%
ENVIRONMENTAL	
Ambient Light	0 to 86,100 lux
Drop Resistance	Withstands repeated drops from 1.2 m / 4.0 ft onto a concrete surface
ESD Protection (Air Discharge)	25 kV
Humidity (Non-Condensing)	5 - 95%
Particulate and Water Sealing	IP52
Temperature	Operating: 0 to 40 °C / 32 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F
INTERFACES	
Interfaces	USB Keyboard; USB COM; OEM (IBM) USB; RS-232
PHYSICAL CHARACTERISTICS	
Colors Available	Black; White (available in presentation version only)
Dimensions (W x D x H)	Tilting Riser: 7.6 x 7.8 x 14 cm / 3.0 x 3.1 x 5.5 in Kiosk/OEM: 10.3 x 5.7 x 11.9 cm / 4.1 x 2.2 x 4.7 in
Weight	Tilting Stand: 345 g / 12.2 oz Kiosk/OEM: 200 g / 7.0 oz

ACCESSORIES

Mounts/Stands



Magnetic Mount 90ACC0384

READING PERFORMANCE	
Aiming	LED aimer for precision scanning
Image Capture	1 MP; 1280 x 800 pixels; Graphic Formats: JPEG, BMP
Print Contrast Ratio (Minimum)	25%
Reading Angle	Pitch: +/- 70°; Roll (Tilt): 0 - 360°; Skew (Yaw): +/- 70°
Reading Indicators	Beeper (Adjustable Tone and Volume); Datalogic 'Green Spot' Good Read Feedback; Good Read LED
Resolution (Maximum)	0.130 mm / 4 mils
READING RANGES	
Typical Depth of Field	Printing resolution, symbol length, scan angle, contrast and ambient light dependent. 1D / Linear Codes 5 mils: 2.5 to 11.0 cm / 1.0 to 4.3 in 7.5 mils: 0 to 15.0 cm / 0 to 5.9 in 10 mils: 0 to 18 cm / 0 to 7.1 in 13 mils UPC: 0 to 21.0 cm / 0 to 8.3 in 20 mils: 0 to 28.0 cm / 0 to 11.0 in 2D Codes 10 mils PDF: 0 to 18 cm / 0 to 7.1 in 10 mils Data Matrix: 1.0 to 13 cm / 0.4 to 5.1 in 15 mils Data Matrix: 0 to 19 cm / 0 to 7.5 in
SAFETY & REGULATORY	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
Environmental Compliance	Complies with EU RoHS, China RoHS and UAE RoHS
LED Classification	EN62471 and IEC62471 Lamp Illumination
UTILITIES	
Scanner Configuration	Aladdin can be used for scanner configuration. Available for download at no charge.
OPOS / JavaPOS	OPOS and JavaPOS utilities are available for download at no charge.
Remote Host Download	Lowers service costs and improves operations.
WARRANTY	
Warranty	3-Year Factory Warranty

MAGELLAN 1500i



INDUSTRY - APPLICATION

Retail:

- Point-of-Sale
- Mobile Marketing
- Age Verification
- 2D bar codes

Commercial Services:

- Postal
- Banks
- Public Administration
- Utilities

Healthcare:

- Patient Bedside Care
- Laboratory
- Pharmacy
- Admittance, Accounting and Billing

OEM:

- Self Checkout
- Customer Service Kiosk
- Price Verification
- Boarding Pass
- Access Control
- Admission Turnstiles
- Parking Machines

DECODING CAPABILITY	
1D / Linear Codes	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code, Data Matrix, MaxiCode, QR Code
Postal Codes	Australian Post; British Post; Canadian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post
Stacked Codes	GS1 DataBar Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; Micro PDF417, PDF417
Digital Watermarks	Optional support for Digimarc® Barcodes/GS1 DW Code
ELECTRICAL	
Current	Operating (Typical): < 500 mA Standby/Idle (Typical): < 300 mA
Input Voltage	5 VDC +/- 10%
ENVIRONMENTAL	
Ambient Light	0 to 86,100 lux
Drop Resistance	Withstands repeated drops from 1.2 m / 4.0 ft onto a concrete surface
ESD Protection (air discharge)	25 kV
Humidity (Non-Condensing)	5 - 95%
Particulate and Water Sealing	IP52
Temperature	Operating: 0 to 40 °C / 32 to 104 °F Storage/Transport: -40 to 70 °C / -40 to 158 °
INTERFACES	
Interfaces	USB Keyboard; USB COM; OEM (IBM) USB; RS-232
PHYSICAL CHARACTERISTICS	
Colors Available	Black; White (available in presentation version only)
Dimensions	Tilting Riser: 6.0 x 7.5 x 13.8 cm / 2.4 x 3.0 x 5.4 in Fixed Riser: 6.0 x 7.5 x 10.6 cm / 2.4 x 3.0 x 4.2 in Wall Mount: 6.0 x 7.5 x 8.4 cm / 2.4 x 3.0 x 3.3 in
Weight	Tilting Stand: 240 g / 8.5 oz Fixed Riser: 164 g / 5.8 oz Wall Mount: 170 g / 6 oz

ACCESSORIES

Mounting Options



90ACC0401 Round Stand, Silver Base, White Scanner
90ACC0400 Round Stand, Black Base, Black Scanner
90ACC0402 Round Stand, Silver Base, Black Scanner



90ACC0379 Tilting Stand, White
90ACC0378 Tilting Stand, Black



90ACC0380 Riser Stand, Black
90ACC0381 Riser Stand, White



90ACC0383 L Bracket/
Wall Mount, White
90ACC0382 L Bracket/
Wall Mount, Black



90ACC0384 Magnetic Mount

Miscellaneous

