Smart Commercial Pad

SUNMI CPad —

One PAD. Business Redefined.















Three Size Options, Sleek and Sturdy








11" Effortlessly Versatile



14" Large Display



Professional Features







Impressive Performance



Wi-Fi 6E & Hyper Wi-Fi & Dual Antenna

Stable Network Connection







Bluetooth 5.3 & SUNMI Exclusive Protocol

Stable Accessory Connection





Innovative Quick Lock on Device Back



Use its magnetic feature and snap-on design for easy accessory attachment and removal—secure and convenient.

Comprehensive accessory solutions for multiple scenarios.

Mobile Accessories. Ideal for mobile operations.







Make CPad your new desktop ECR with bases that are easy to install and remove.







Use table-side stands that are sturdy, power bank compatible, and fit various desktop settings.







Mount Adapter



SUNMI CPad Tech Specs

CPU

Octa-core, up to 2.4GHz

os

SUNMI OS 4.0 (Based on Android 14)

Memory

4GB RAM + 64GB ROM 8GB RAM + 128GB ROM Extended Micro SD Card Slot Up to 256GB

Displays

11" WUXGA, 1920*1200 Pixels, IPS Multi-Touch Capacitive Touch Screen

GMS

Supported (Optional

Buttons

1*Power button

Card Slots

Wi-Fi version: 1*MicroSD 4G version: 1*Nano SIM +

eSIM

Supported (Optional)

Interface

2*Type-C 6*Pogo PIN at the bottom for connecting accessories 8*Pogo PIN on the back for connecting accessories

Cellular

G/3G/2G

Wi-Fi

6GHz/5GHz/2.4GHz IEEE 802.11 ax/a/b/g/n/ac 2*2MIMO

Hyper Wi-Fi

Supported (Optional)

Bluetooth

Bluetooth 5.3, Support BLE

Positioning

GPS/Glonass/Beidou/Galileo

Cameras

5MP FF Front Camera + 8MP AF Rear Camera 5MP FF Front Camera + 13MP AF Rear Camera

Scanner

Professional 2D Scan Engine (Optional)

NFC

Supported (Optional)
Tap on screen
Support SOFTPOS, EMVCo
PCD L1 Compliant
Support ISO/IEC 14443
TypeA/B, Mifare, Felica,
ISO 15693
Support NFC tag

Fingerprint

Supported (Optional)

Audio

2*Speaker 2*Microphone

LED Indicator

Supported

Battery

Non-removable Lithium Polymer Battery 4.45V/8000mAh

Sensors

Gravity sensor Light sensor Proximity sensor Geomagnetism (Optional)

Adapter

Input: 100V-240V AC Output: 9V2A/5V2A DC

Dimensions(L*W*H)

256.1*168.2*10.1 mm

Net Weight

526a

Protection

IP54

Environment

Operating Temperature: -10°C to 50°C Storage Temperature: -20°C to 60°C Operating Humidity: 5% to 95% non-condensing

Accessories (Optional)

Desktop Base Printing Base Multi-Function Pivoting Base Table-Side Fixed Stand Table-Side Stand External Barcode Scanner Hand Strap and Mount Protective Case Mount Adapter 4-Slot Charging Base Desktop Stand Shoulder Strap

^{*}The 8.7" and 11" PADs are not yet available, and their accessories are not fully launched. For specific release dates, please contact the sales reps of your region

^{*}This product description is based on the current information available at the time of launch. Due to product upgrades or other reasons, the content may change. The company reserves the right to modify the product and content without prior notice