# EZ-LP™ Desktop Label Printer







### **EZ-LP**

#### Keep your code. Choose your printer.™

Change is good... when it's easy, better, and costs less. The CognitiveTPG EZ-LP desktop printer is your alternative to more expensive legacy printers, providing a better value with drop-in compatibility. The EZ-LP is a 4" wide direct thermal printer that comes standard with a durable print mechanism, extensive flash memory, 5" media roll capacity, and multiple communication interface options and programming emulations. The EZ-LP is ideal for a wide range of applications, including work-in-process (WIP), logistics, and retail.



Optional Serial/Parallel/USB Communications Shown

- The best choice to refresh legacy ZPL and EPL desktop applications
- Robust ZcPL and EcPL emulations
- Industry standard communication interfaces (serial, parallel, USB, and Ethernet)
- Only standard USB-A (host) port in its class
- Rugged field proven mechanical design
- 4" model (4.25" media width)
- 203 dpi (8 dots/mm) DT print mode

### **EZ-LP**

## Keep Your Code. Choose Your Printer.

#### **Technical Specifications**

PRINT	
Method	Direct Thermal
Width (max)	4.1"/104 mm
Length (max)	322" (8179 mm) at 203 dpi
Speed (max) Resolution	5 ips (127 mm/sec)
	203 dpi (8 dpmm)
MEDIA	
Width	2" - 4.25" (50 - 108 mm)
Roll Diameter	5.0" (127 mm)
Indexing	Black bar, notch, and gap
BAR CODES	
EcPL ZcPL	Code39, Code39 with check digit, Code93, Code128 Auto A/B/C, Codabar, EAN8, EAN8 with 2/5 digit add-on, EAN13,
	EAN13 with 2/5 digit add-on, Interleaved 2 of 5, Postnet, UCC/EAN 128, UPC A, UPC A with 2 digit add-on, UPC E,
	UPC E with 2/5 digit add-on, Aztec, DataMatrix, MaxiCode, PDF417
	Code 11, Interleaved 2 of 5, Code 39, Planet Code, PDF417, EAN-8, UPC-E, Code 93, Code 128 (Subsets A,B, and C),
	UPS MaxiCode, EAN-13, Micro-PDF417, Industrial 2 of 5, Standard 2 of 5, ANSI Codabar, LOGMARS, MSI, Aztec, Plessey, QR Code, RSS,
	UPC/EAN Extensions, UPC-A, Data Matrix, Bar Code Field Default, POSTNET
FONTS	
EcPL	5 bitmapped fonts, up to 8x magnification
ZcPL	15 bitmapped fonts, one scaleable font
GRAPHICS	Ability to upload and recall. PCX and BMP formats
MEMORY	RAM - 8 MB, Flash - 4 MB
COMMUNICATIONS	
Standard	Serial (DB9) and USB (A&B)
Optional	Serial (DB9)/Parallel (Centronics) and USB (A&B)
	Ethernet (internal) and USB (A&B)
ELECTRICAL	Auto-ranging 100-240 VAC, 50-60 HZ, 24VDC output
ENVIRONMENTAL	
Operating	41°F to 104°F (5°C to 40°C)
DIMENSIONS	6.85" (174mm) W x 6.9" (175mm) H x 9.7" (246mm) D
WEIGHT	3.9 lbs (1.77kg)
ACCESSORIES	
Standard	QuickStart Guide, power supply and cord, user quide, Cognitive Administrative Utility and Window's driver
Optional	Parallel port, communications cables, label (peeler) dispenser, Ethernet, real-time clock
WARRANTY	

12 months from date of purchase (requires registration and excludes printhead)

EcPL and ZcPL language emulation

EPL is a Zebra trademark. Zebra and ZPL are registered trademarks of ZIH Corp.



PROGRAMMING LANGUAGE

Printer

950 Danby Road, Suite 200, Ithaca, NY 14850
Toll Free: 800.732.8950 Phone: 607.274.2500 Fax: 607.274.2449
www.CognitiveTPG.com
Copyright 2012 CognitiveTPG. All Rights Reserved.

