TARGETED TO DISTRIBUTION & RETAIL MARKET



SUPER ULTRA RUGGED!

1.8M DROP TESTED IP 65

Excellent Performance yet Rugged;

Built for year round use in nearly any environment, with IP65 sealing and the ability to survive a 1.8m drop to concrete. You can count on reliable operation inside and outside the enterprise and still deliver dependable performance. The IP65 sealing rating enables use in dusty environments and exposure to rain or spills. The result is a dramatic reduction in repair requirements and downtime.

FEATURE RICH!

WLAN IEEE 802.11 a/b/g WINDOWS CE 5.0 806MHz CPU PROCESSOR 3.0M PIXELS CAMERA 4,800mAh BATTERY

M3 T provides all the features users need and more!;

The M3 T designed for complex applications and seamless communication with incredible speed, from Wi-FI WRAN 802.11 a/b/g with complete security to industry standard software application with Windows CE 5.0. It delivers Memory ranging from 256MB RAM / 256MB(Max.1GB) ROM for plenty of memory for multi-tasking in today's high output business world, a 3.0 megapixel camera for the rich data capture and 4,800mAh battery for a full shift of real world productivity.

M3 T Ergonomically designed for optimal field use and optimized for ambidextrous single handed operation with a scan button in the middle.









■ M3T (MC-6700S) SPECIFICATION



MODEL NO.			M3 T
			MC-6700S
PERFORMANCE CHARACTERISTICS	CPU	Spec	PXA320 806MHz
	OS	Spec	Windows CE 5.0
	MEMORY	RAM	256MB
		ROM	256MB(up to 1GB)
PHYSICAL CHARACTERISTICS	Dimension(W x H x D)		77 x 168.8 x 28 mm (including std. battery) 77 x 168.8 x 34.5 mm (including ext. battery)
	Weight		13.3oz / 378g (including std.battery) 14.9oz / 424g (including ext.battery)
	DISPLAY	Туре	3.5 " QVGA TFT type, 260k colors
	KEYPAD OPTIONS		Numeric
	BATTERY	STANDARD	Li-polymer 3.7V 2,700mA/h
		EXTENDED	Li-ion 3.7V 4,800mA/h
	EXPANSION SLOT		MicorSD card(up to 8G)
	SCANNER	1D	1D Laser
		2D	2D Imager
	CAMERA	Spec	3.0M pixel AF
		Flash	O(Led)
	ETHERNET		O(via cradle)
INTEGRATED RADIO	WLAN RADIO	Radio	802.11 b/g, 802.11 a/b/g
	WPAN RADIO	Bluetooth Spec	Class II Ver. 2.0 + EDR
	GPS	Spec	Integrated GPS
USER ENVIRONMENT	TEMP	OPERATING	-4°F to 140°F / -20℃ to 60°C
		STORAGE	-22°F to 158°F / -30°C to 70°C
		HUMIDITIY	90% non-condensing
	DROP Specification		6ft. / 1.8m Drop to steel suface, 2 drops per 6 sides
	RAIN/DUST PROTECTION		IP65
	Accessory		Sing Slot Serial Cradle, Single Slot Ethernet Cradle, Four Slot Ethernet Cradle, Four Slot Cradle, Car Cradle, Standard Battery(Li-polymer 2,700mA/h), Extended Battery(Li-ion 4,800mA/h), AC Cord, Adaptor, USB Cable Stylus Pen, Ear-Phone, Leather Case

Distributed by



Your Best Mobile Business Partner

M3 Mobile Co.,Ltd

Sales H.Q: 135-080, M3 Bldg. 735-45 Yeoksam-Dong, Gangnam-Gu, Seoul, Korea

Tel +82-31-574-0037 Fax +82-2-578-9809
Email : sales@m3mobile.co.kr Http://www.m3mobile.net
Factory : 420-120, Chuneui-Technopark || , 202 Chuneui-Dong, Wonmi-Gu, Bucheon, Korea Tel +82-32-623-0037 Fax +82-32-655-0884

R&D Center: 135-080 Dongwon Bldg. 725-30, Yeoksam-dong, Gangnam-gu, Seoul, Korea Tel: +82-2-574-0037 Fax: +82-2-578-9809

E-mail: sales@m3mobile.co.kr