METAPACE <u>Metapace T-3 – Economical fully equipped top quality printer</u>

Highlights

- Extremely reliable direct thermal printer with a 5-year warranty
- Lightning-quick printing of slips and receipts with up to 250 mm/sec.
- Easy connection via integrated USB port
- Versatile options: serial, parallel, Ethernet and Wi-Fi
- Entirely out-of-the-box: just unpack and start

Technical specifications

Print	
Printing method	Direct thermal
Print speed	Max. 250 mm/s
Consumables	Thermal paper
Paper	Width: 79.5 mm +/- 0.5 mm, max. Ø: 83 mm
Print width	Up to 72 mm
Paper supply	Easy paper loading
Resolution Character sizes	7 dots/mm (180 dpi)
Barcodes	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24 All standard 1D and 2D barcodes
Electronics	All standard TD and 2D barcodes
Emulation	ESC/POS
Sensor	Paper near end, paper end, cover open
Memory	64 Mbit SDRAM, 16 Mbit flash ROM
Power Supply	External, 100–240 V AC, 50/60 Hz
Reliability	150 km TPH, 1,800,000 cuts, 70,000,000 lines
Interfaces	
I/F ports	Integrated USB 2.0 and cash drawer port (RJ12), RS232, LPT, Ethernet,
	WLAN (optional)
Software	
Operating system	Window XP (32/64-bit), Server 2003 (32/64-bit), Vista (32/64-bit), Server 200
	(32/64-bit), 7 (32/64-bit), 8 (32/64-bit), Linux, MAC, VCOM, OPOS, JPOS
SDK	Android (version 2.2 or higher), iOS (version 5.1.1 or higher)
Housing	
Dimensions (WxDxH)	148 x 200 x 150 mm
Colour	Black
Warranty	
Period	5 years
Specifics	
Package contents	USB cable (A/B), PSU + power cord (EU), CD (drivers, utilities), QSG, splash-proof cover, cable cover, cleaning pen, buzzer, test receipt roll

METAPACE

Direct Thermal RECEIPT PRINTER