

OPR4001

Barcode CCD scanner

RS232

Keyboard Wedge

 USB



+ Related products

OPT6125

- Cabled device
- Barcode CCD scanner
- RS232, Keyboard Wedge, USB

OPR2001

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB
- With auto-trigger stand

OPL7836

- Cabled device
- Barcode laser scanner
- RS232, Keyboard Wedge, USB

Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

Operating keys

- Entry options:
1 scan key

Communication

- RS232: DB9 PTF connector with external power supply
- Keyboard Wedge: MiniDIN6 connector
- USB: Ver. 1.1, HID/VCP, USB-A connector

Power

- Voltage requirement: 5 V \pm 10% (Keyboard Wedge and USB), 6 V (min. 4.5, max. 6.6 V) (RS232)

Barcode scanner Optics

- Light source: 626 nm red LED
- Scan method: CCD linear Sensor 2500 Pixels
- Scan rate: 200 scans/sec
- Trigger mode: Manual, auto-trigger

Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSM-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Composite codes, MicroPDF417, PDF417

Durability

- Temperature in operation: 0 to 50 °C / 32 to 122 °F
- Temperature in storage: -20 to 60 °C / -14 to 140 °F
- Humidity in operation: 5 - 95 % (non-condensing)
- Humidity in storage: 5 - 95 % (non-condensing)
- Ambient light immunity: Direct sun 10,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 10 - 100 Hz with 2G for 1 hour
- Protection rate: IP 42

Physical

- Dimensions (w x h x d):
52 x 165 x 77mm / 2.05 x 6.50 x 3.03 in
- Weight body: Ca. 80 g / 2.8 oz (excl. cable)
- Case: ABS, White

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

Enclosed items

- Power supply 6V/2A (for RS232)

Models

- Interface versions: RS232, Keyboard Wedge, USB
- Color versions: Black, White

Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg, NY - Seattle, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong

Opticon Sensors Europe B.V.
European headquarters
Opaalaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON

WWW.OPTICON.COM