



# M10e



## ***Maximum Printing – the SATO M10e***

SATO's wide web printer is just as big on performance as it is in size. With a print speed of up to 125mm/sec (5ips) and an ultra high speed data processor, the M10e meets the needs of a range of industries, including shipping and logistics, petrochemical and paper and timber production.

- ✓ **267 mm wide print area**
- ✓ **305 dpi print resolution**
- ✓ **Ultra fast processing**
- ✓ **Heavy-duty construction**
- ✓ **Large standard memory**

**Maximum Printing** – The SATO M10e has a print width of up to 267mm (10.5") and can hold label sizes up to 300mm (11.8") wide x 423mm (16.6") long.

**Maximum Throughput** – The 32-Bit high-speed RISC processor at the heart of every M10e printer ensures fast data transmission and almost instantaneous throughput, resulting in unparalleled label production speed.

**Maximum Durability** – Built to survive harsh industrial environments, the casing will keep out dust and dirt. The main components are also solidly constructed, ensuring maximum durability and endurance.

**Maximum Connectivity** – The wide choice of interfaces allows the M10e to connect to almost any system.

# M10e

|                   | M10e   |
|-------------------|--|
| Printing Method   | Thermal Transfer / Direct Thermal  |
| Print Resolution  | 12 dots/mm (305 dpi)   |
| Print Speed       | Up to 125mm/sec (5 ips)  |
| Max. Print Width  | 267mm (10.5")  |
| Max. Print Length | approx. 420mm (16.5")  |
| Media Size        | Min. 131mm (5.16") W x 43 mm (1.7") L<br>Max. 300mm (11.8") W x approx. 423 mm (16.6") L |
| Dimensions        | 475mm W x 315mm D x 320mm H<br>(18.7" W x 12.3" D x 12.6" H)                             |
| Weight            | 21.2kg (46.7 lbs.)   |

#### Memory:

- 16 MB SDRAM Memory with RAM
- 2 MB Flash Memory
- 6 MB Flash Memory (option)

#### Processor:

- 32-BIT RISC, 118 Mhz

#### Modular Interface Options:

- ECP parallel – IEEE1284
- RS232C high speed up to 57,600 baud
- USB (12Mbit/s)
- LAN (TCP/IP protocol 10/100 Base T)
- RS422/485
- LAN 802.11b wireless

#### Media:

Roll or fan-fold die-cut labels

- Max. Caliper 0.21mm (0.008")
- Max. Inner Diameter 76.2mm (3")
- Max. Roll Diameter 200mm (7.8")
- Wind Face-In

#### Bar code Symbolologies:

- Linear: UPC-A/E, EAN-8/13, Code 39/93/128, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/EAN 128
- 2-Dimensional: PDF417, Micro and Truncated PDF 417, Maxicode, Data Matrix, QR Code, RSS-14

#### Bar Code:

- 2:1, 3:1, 5:2 ratio; programmable height up to 999 dots

#### Human Readable Fonts:

12 proportional, mono-spaced and outline fonts (Code page 858, others available). Internal CG Triumvirate<sup>®</sup> and CG Times<sup>®</sup> fonts plus downloaded TrueType<sup>®</sup> fonts

#### Self Diagnosis Check Features:

Head, Paper-End, Ribbon-Near-End, Ribbon End, Head Open, Memory Card Error, Test Print, Cutter Cover Open

#### Other Features:

Status Report, Graphics, Sequence, Form Overlay Store, Custom Design Character, Reverse Image, Line Print, Hex Dump Print, Format Store, Paper Auto Loading

#### Power:

- 115V / 230V AC, 560VA

#### Options:

Cutter, Real Time Clock, Stacker, Unwinder, Smart Keyboard

## Sales Support

If you would like to discuss your needs in more detail or arrange a demonstration, please contact our sales team:

SATO UK Limited. Valley Road, Harwich, Essex CO12 4RR

Tel: +44 (0)1255 240000 Fax: +44 (0)1255 240111

E-Mail: [enquiries@sato-uk.com](mailto:enquiries@sato-uk.com)

Web: [www.sato-uk.com](http://www.sato-uk.com)



SATO makes no guarantee that the above features are available in all models and specifications are liable to change without notice.