



NEXUS N-3030

The choice of every retailer

Setting the new benchmark for omni-directional scanning, the Nexus N-3030 takes an unique position in the market. With an unequalled 2480 scans/second and an unique scan pattern of 24 scan lines, the Nexus is the choice of every retailer who wants to optimise counter environment with a winning scanner performance and a great design! The special flexible stand enables the retailer to position the scanner to the wishes of the operator, ensuring an ergonomic use. The Nexus is ideally suited for drugstores, pharmacies, department stores, petrol stations and supermarkets. Special stitching software enables it to read poorly printed and damaged codes, an USB interface connects it to the latest POS-systems and the Nexus is equipped with an EAS deactivation antenna to ensure compatibility to all RF security systems.

transparent



solid

unique



General information

The Nexus N-3030 is the benchmark for presentation scanning. The 7 directions scan field of the Nexus generates a large volume reading zone with a scan pattern of 24 lines, ensuring high performance omni-directional scanning. Scantech's new Scantium MMX decoder chip gives the Nexus an unrivalled multi-decoding power.

Cost of Ownership

The Nexus features Scantech's unique and patented Goldrush polygon technology. Evaporated gold on the polygon makes it ultra light, giving longer motor life and faster 'wake-up' times from the energy saving sleep mode. In addition, a flash EPROM gives the possibility to upgrade the firmware within the twinkling of an eye.

Reading of damaged and out-of-spec codes

Special STAR software enables the Nexus to easily read truncated and substandard codes from a distance as well as on the window. Even damaged or frozen food codes are no problem for the special code stitching intelligence of the Nexus. Furthermore, the Nexus is the benchmark for reading EAN/UPC AddOn codes.

Ergonomics and ease of use

The Nexus can be installed fixed on a counter surface or on a flexible, rotating stand. The stand can be rotated and tilted in the direction that the operator likes it best to work with in order to optimise efficiency at the checkout. The flexible stand also has a cable guide through the centre to cleverly connect the cables to the scanner without leaving them into sight on the counter.

Flexibility

The Nexus comes in two interface versions: RS232/OCIA or IBM RS485/Keyboard Wedge and USB. This makes multiple installations and migration from one PoS system extremely easy. An auxiliary port for connecting a hand held scanner is standard, just as the EAS deactivation antenna for the use with RF security systems.

NEXUS N-3030

specifications

Physical depth: 61 mm • width: 135 mm • height: 146 mm • weight: 500 grs • (without stand: depth 135 mm • width 135 mm • height 215-237 mm • weight 675 grs)


Dual interfaces RS232C - OCIA • IBM RS485 - KBW - USB **Electrical** power supply voltage: 100 - 240 V ac • 50/60 Hz • DC input to scanner: 5,2 V dc (450 mA) or 8 - 16 V dc (3 Watt) **Optical** light source: visible laser diode 630 -670 nm 7-field, 24 line scan pattern • scan rate: 2480 scans/second • depth of scan field: 300 mm

Operating environment 0°C to 40°C • humidity: 0% - 95% RH (non-condensing) **Supported codes** EAN/UPC/JAN including AddOn • Code 128 • EAN 128 • Code 39 • Code 93 • Code 32 (lt. Pharmacode) • Codabar • interleaved 2/5

Safety The Nexus N-3030 complies with:

- laser safety IEC 825-1 (1993) Class I, U.S. CDRH: 21CFR1040 Class IIa
- electrical safety EN 60950 (second edition), UL 1950, c-UL (according CSA22.2.950)
- radio and tv interference EN 55022 Class B (1994), FCC part 15 Class B (1992)
- radio frequency immunity EN 50082-1 (1992)

Specifications may change without prior notice.



SCANTECH ID

Scantech-ID BV

Amersfoortsestraat 124

3769 AN Soesterberg

The Netherlands

Tel +31 (0)33 469 84 00

Fax +31 (0)33 465 06 15

info@scantech-id.com

www.scantech-id.com

