

Ultimate quality scanner

Looking for a high quality scanner which offers a great performance at a great price? Get the MS837 and enjoy the long life time, ergonomic design and high reliability. It's a great scanning solution for a broad range of markets and application such as point-of-sale, retail, access control and hospitality.

Top quality reading performance

The MS837 offers a top quality laser engine for a snappy, high-quality scanning performance. The long working range and wide scan field make sure users can easily scan all standard 1D and GS1 databar symbologies with the MS837. Precise targeting of the laser scanner ensures quick, one-time scanning of barcodes for a smooth operation. This high cost-effective laser scanner will increase productivity of many high demanding scanning applications.

Robust and elegant design

The MS837 has an ergonomic design and trigger button which makes the scanner very user-friendly. This ergonomic design

and weight of only 120 grams makes the MS837 fit comfortably in any hand, reducing fatigue during long-time scanning tasks. The 1m drop specification onto concrete limits downtime and cost of ownership. Both you and your employees will be happy working with this scanner!

Great scanner - great price

Enjoy the superior performance of the MS837 high quality laser scanner at a very compatitive price. It becomes even more compatitive since a hand-free stand is included.

Main features

- Top quality renowned scan engine snappy performance
- Ergonomic trigger button and form factor
- Lightweight: only 120 grams
- Robust design: 1m drop spec.
- Reads all common 1D barcodes and GS1 symbologies
- Quick and easy connection to host computer/pc
- Hands-free stand included



Operational & Performance

Technology Laser engine

Light Source Visible Laser Diode 650nm

Resolution (max.) 4mil/0.1mm

Print Contrast 35% min. reflectance difference

Scan rate 72 scans/sec

46° (typical), 35° +/- 3° (narrow) Scan angle

Reading distance (DOF PCS=80%)

Label/DOF	near	far
Code 39, 5mil	7.6cm	12.7cm
Code 39, 7.5mil	5cm	20.3cm
Code 39, 10.4mil	2.5cm	22.8cm
Code 39, 13mil	1.2cm	25.4cm

^{* =} dependents on width of barcode

Symbologies

Decode Capability Code 39, Full ASCII Code39,

Interleave 2 of 5, Standard 2 of 5, China Postal, UPC, Delta Code, MSI, Plessy, Codabar, Code 11, EAN8/13, Code 93, Code 128, EAN128, Code32, Italian Pharmacy, Label Code, GS1

databar code

Operation mode

Trigger Mode, Auto scan Mode

Connectivity

USB, Keyboard wedge

Enclosure

Scanner dimension 153mm x 70mm x 110mm Scanner weight 120g (without cable)

Environmental

Operating temperature 0°C to 40°C Storage temperature -40°C to 60°C

5% - 90% non-condensing Humidity Drop test to concrete

1 meter

Accessories

Hands Free Stand

Warranty

2 years (EU)

* Check conditions when Non-EU

Regulatory approvals

CE, FCC, BSMI

Unitech Europe

Tilburg, The Netherlands

• Tel.: +31 (0)13 460 9292

• Email: Info@eu.ute.com

• Website: http://eu.ute.com





Unitech America Unitech Asia Pacific Unitech China Unitech Europe Unitech Japan Unitech Taiwan