

While the workload and healthcare quality standards are getting higher, hospitals and other medical environments are desperately in need of the latest techniques to offer the best care possible. When people's lives are at stake every mistake is one too many. The PA690 MCA helps healthcare workers do their jobs accurate, quick and responsible, whether its regarding patient care, access control or laundry management. This device offers the next level in healthcare technology; it's the ultimate Mobile Clinical Assistant: PA690 MCA.

Healthcare challenges

The biggest healthcare challenges are the reduction of human errors and a proper administration of every step of the care process. All of this and more can now be done efficiently with the PA690 MCA. This device meets all possible requests of healthcare workers. The anti-microbial housing of the PA690 MCA makes sure this device can be used within healthcare environments following high hygienic regulations. Because of the integrated 2D imager and optional RFID reader the device can be used in multiple ways. Next to inventory control to avoid out-of stock situations and patient care, the PA690 MCA is the ideal solution for asset management, parking and waste management as well. The device can also be used perfectly for voice note recording.

See more in healthcare surroundings

The 3.8" WVGA LCD touch screen brings the healthcare workers massive user benefits. The PA690 MCA can show all latest care information as well as medication instructions in one single screen view. Because of the latest communication technology the database is always up-to-date providing 100% accuracy in information recording. Taking care of patients has never been so easy and straightforward, reducing time and costs. The 1.5m drop specification and IP65 sealing limits the downtime and repair costs of this assistant to the minimum.

Increase the safety of your patients, reduce human errors and costs and provide your employees with the best possible technology available. Try it yourself and be convinced!

Main Features

- Anti-microbial housing
- Integrated 2D imager, optional HF-RFID reader
- 3.8" WVGA LCD touchscreen
- Rugged: IP65 & 1.5m drop spec
- 2.200mAh battery and an optional 4.000mAh
- USB 1.1, BT 2.1+ EDR, WLAN 802.11 a/b/g (CCX4)
- 5.0 megapixel autofocus camera with flash
- Rich set of accessories







Operation System

CPU Marvell PXA320 806MHz **RAM** Mobile DDR 256MB **ROM** NAND flash 512MB

Windows Embedded Handheld 6.5 Classic OS

Display

3.8" full WVGA transflective color LCD touch screen with backlight -

246 DPI - 800 x 480

Camera / Photos / Vldeo

5.0 megapixel autofocus camera with flash

Unitech MPEG-4 video codec

Keypad

26 numeric keypad

6 side keys (programmable with 12Remap)

Indicator

Leds

Vibrator

Integrated reading devices

2D imager, HF-RFID reader (optional)

Symbologies

2D Imager

1D codes

Various postal codes, Codabar, Code 11, Code128/EAN 128, Code 39, Code 93, EAN13, EAN 8, IATA 2 of 5, Matrix 2 of 5, MSI, Planet code, Postnet, RSS, expanded & limited, RSS14, UPC A, UPC E, UPC E1

2D codes

Aztec, Codablock F, Code 49, Datamatrix, EAN-UCC Composite, Maxicode, Micro PDF417, PDF-417, QR Code, Tcif lonked C39

HF-RFID

HF 13.56MHz supports ISO15693, ISO14443 A/B

Communication

USB 1.1 Host & Client **USB**

WLAN IEEE 802.11 a/b/g , CCX4 Compliant

PAN Bluetooth 2.1 + EDR

Power Source

8.14 Watt-Hour 3.7V@2200mAH Main Battery

12.21 Watt-Hour 3.7V@4000mAH Date/time retention - 2 hours - 40mAh

Backup Battery Operating time 1 scan/ 5 sec. - 6-10 hours

Audio

Speaker 1W - Mono

Headset Connector 3.5mm 4 pole; L/R speaker & mic

Receiver

Microphone Dual, with echo cancelation and noise reduction

Expansion Slot

Micro SD support SDHC up to 32GB Dual Micro SD slots in HF RFID model

Unitech Europe

Tilburg, The Netherlands

• Tel: +31 (0)13 460 9292

• Email: Info@eu.ute.com

Website: http://eu.ute.com





Weight 390g with 2200mAh battery 430g with 4000mAh battery

Appr. 177.66mm x 74.58mm x 40.41mm Dimension

(Antenna lenght excl.)

Environmental

-10°C to 50°C Operating temperature Storage temperature -20°C to 60°C

Relative Humidity 5% ~ 95% (non-condensing)

Drop Specification 1.5 meter Sealing **IP65**

Anti-Microbial casting Reference U.S. Pharmacopeia 26

NF 21, Microbiological Tests (51) Antimicrobial Effectiveness Testing

Software

Microsoft Visual Studios 2005/2008 Auto Installer

12Manage & 12Solutions



In-house developed software to enhance device deployment and remote management. 12[want:to]Solutions including 12Manage improve system reliability, reduce service costs and ensure systems running smootly.

More info: www.unitechnical.info

Accessories

USB charging and communication cradle Ethernet charging and communication cradle 4-slots battery charger 4-slots multi-bay Ethernet cradle USB charging and communication cable RS232 charging and communication cable AC adaptor Mono 3.5mm headset

Regulatory Approvals

CE, FCC, BSMI, VCCI, CCC, RoHS compliance



Unitech's service program

UnitCare offers customers a high level of security by a reliable, high-quality and effective program for getting your devices serviced quickly. It also drives the hidden costs out of your installations. UnitCare goes beyond the standard warranty with a complete service offer for different need.

More information: www.unitcare.info



Unitech America Unitech Asia Pacific Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan