




VASARIO SERIES

PRODUCT SPECIFICATIONS



ELECTRONICALLY OPERATED (Dual Media)

I915 MODEL



Dimensions:
(width x depth x height)

18.8 x 15.2 x 4.3 inches
478 x 386 x 110 mm


Height without feet:

3.8 inches or 97 mm

Shipping weight:

22 lbs
10 kg

I618 MODEL



Dimensions:
(width x depth x height)

16.2 x 18.3 x 4.3 inches
411 x 466 x 110 mm


Height without feet:

3.8 inches or 97 mm

Shipping weight:

21 lbs
9.5 kg

I616 MODEL



Dimensions
(width x depth x height)

16.2 x 16.3 x 4.3 inches
411 x 415 x 110 mm

Height without feet


3.8 inches or 97 mm

Shipping weight

19 lbs
8.6 kg

ELECTRONICALLY OPERATED (Non-Media)

I416 MODEL



Dimensions
(width x depth x height)

13.8 x 16.3 x 4.0 inches
351 x 415 x 102 mm

Height without feet


3.5 inches or 89 mm

Shipping weight

16 lbs
7.3 kg

MANUALLY OPERATED (Non-Media)

I616 MODEL



Dimensions
(width x depth x height)

16.2 x 16.3 x 4.3 inches
411 x 415 x 110 mm


Height without feet

3.8 inches or 97 mm

Shipping weight

19 lbs
8.6 kg

I416 MODEL



Dimensions
(width x depth x height)

13.8 x 16.3 x 4.0 inches
351 x 415 x 102 mm

Height without feet

3.5 inches or 89 mm

Shipping weight

16 lbs
7.3 kg

FEATURES

- Numerous till configurations available. See our **Standard Duty Accessories brochure** or contact your APG representative for options
- Electronic drawers tested to last beyond one million operations
- Manual drawers tested to last to 300,000 operations
- Under till storage area
- Available in Black and Beige, with either a painted or stainless steel drawer front (stainless not available for manually operated drawers)
- Four function lock
- Closed and latched drawer status switch (not available in manual)
- Random keying is standard, other lock and key options available

AVAILABLE INTERFACES

101	Manually Operated Drawer**	554A	USBPro™ II, USB Interface
320	MultiPRO® 24 volt *	484A	SerialPRO® II
420	MultiPRO® II 12 volt *	XXX	Other interface numbers indicate a custom interface

* Requires detachable cable sold separately. Refer to Connectivity Guide at www.cashdrawer.com for interface cable detail.

** Only available for the I416 and I616 models

OPERATING ENVIRONMENT

Storage Temperature	-30°C to +50°C (-22°F to +122°F)	Relative Humidity	10% to 95%
Operating Temperature	0°C to +40°C (+32°F to +104°F)	(non-condensing)	

ACCESSORIES

See our **Standard Duty Accessories brochure** or contact your APG representative for options

1. Tills
2. Locking till covers
3. Weighable coin cups
4. Under counter mounting brackets

WARRANTY

Two (2) year limited warranty. A full warranty statement is available online at www.cashdrawer.com/support/warranty-statement.



APG Cash Drawer, LLC
5250 Industrial Blvd. N.E.
Minneapolis, MN 55421

Phone: 763 571 5000
Fax: 763 571 5771

APG® Cash Drawer, the APG Cash Drawer logo, SerialPRO®, MultiPRO®, DirectPRO®, USBPro™, ParallelPRO™, POS-Integrator™, Vasario™, POS-Podium™ and Cash Drawer Caddy™ are trademarks of APG Cash Drawer, LLC.

M-43-111 Rev. C