



” Modular 15" all-in-one POS system

Specifications – P4100

- Slim POS system for those who value good looks
- Excellent performance thanks to Intel Celeron processor with 2.0 GHz
- Exchangeable interfaces for flexible requirements
- Available with resistive or capacitive touch

		P4100
System	CPU	Intel Celeron J1900 QC 2.0 GHz
	System memory	4 GB SO-DIMM, DDR3L, 1333 MHz, max. 8 GB (1 slot)
	Chipset	Intel Baytrail platform
	Hard drive	Min. 500 GB HDD, SSD optional
	Supported OS	WS7E / POSReady 7 / Windows Embedded 8.1 Industry / Windows 10 / Linux
Display	Graphics chip	Intel HD graphics
	LCD size	38.1 cm (15") LCD
	Max. resolution	1024 x 768 pixels
	Brightness	350 nits, LED
	Touch screen	5-wire resistive, PCAP
Interfaces	USB 2.0	3x (optional up to 6x)
	USB 3.0	1x
	Powered USB	1x (optional, 24 V)
	Serial / COM (RJ45)	4x (optional 5x)
	Parallel	Optional
	LAN	1x Gigabit
	VGA	1x
	Cash drawer port	1x (12 V RJ11)
PSU	Power adapter	Integrated in the stand, 90 watts
Other	Dimensions (WxDxH)	374 x 265 x 339 mm
	Weight	Ca. 6.6 kg
	Operating temperature	0 to 35 °C
	Certification	CE, FCC, RoHS
Options	Mounting options	VESA 100 x 100 mm
	MSR	Yes
	Customer display	Yes (2 x 20 characters, integrated, pole)
	Customer-facing screen	Yes (8", 15", pole)
	Barcode scanner	Yes (1D, 2D)
	Waiter's lock	Yes (iButton)
	RFID	Yes (MiFare)
	Colour	Black, additional colours upon request
	UPS	Optional
	Interface options	In addition to the standard interfaces, the following options are available: Option A (2x USB, 1x UPS, 1x Audio) Option B* (1x RS232, 1x UPS, 1x Audio) Option C (2x USB, 1x 24 V pUSB, 1x Audio) Option D (1x LPT)

*Only in combination with PCAP; factory fitted