



## Glancetron 15L LCD monitor with top-notch features

- Attractively priced 15" LCD monitor with LED backlight
- Integrated touch screen with 5-wire resistive touch technology
- Elegant design and particularly robust construction
- USB interface for simple integration
- Maximale Auflösung: 1.024x768 Pixel

### Specifications

Display	Screen diagonal / type	38.1 cm (15") / LCD TFT active matrix
	Aspect ratio	4:3
	Resolution (max.)	1024 x 768 Pixel
	Active area (WxH)	304 x 228 mm
	Response time	16 ms
	Colours	16.2 million
	Contrast	500:1
	Brightness	250 cd/m <sup>2</sup>
	Viewing angle (H/V)	n/a
	Video input	VGA (analogue)
	Touch technology	Resistive (5-wire)
Touch interface	USB	
General	Colour	Dark grey
	Dimensions (WxHxD)	370 x 350 x 210 mm (incl. foot)
	Weight	7,5 kg / 8,5 kg
	Power supply	External power supply (DC 12 V / 3.33 A)
	Power consumption	Operating: n/a / Sleep: n/a / Standby: n/a
	Mounting options	Stand (not removable)
	Control buttons	Power on/off, Menu/Enter, Left, Right, Auto
	Audio	n/a
	Certifications	FCC, CE, RoHS, Class A, CCC
	Drivers	Windows 10, 8, 7, XP, Linux
	Options	n/a
Delivery contents	Monitor, connection cables (USB, VGA), power supply, power cord (EU), driver CD	
Environment	Operating temperature	0 to +45 °C
	Storage temperature	-20 to +60 °C
	Operating humidity	0 to 80 % (non-condensing)
	Storage humidity	10 to 90 % (non-condensing)

Your partner