

Glancetron 1290 professional magnetic stripe reader



- Professional magnetic stripe reader in extremely compact design
- Reads all three tracks of all credit, EC, customer and many other cards with ISO standard
- Flexibility through diverse connection options (KWB, RS232, USB)
- Versatile programming options
- Available in black or white

Specifications

General	
Decoding Capability	Triple-tracks: tracks 1 & 2 & 3
Card Reading Speed	7.5 to 125 cm/sec, bi-directional
Magnetic Head Life	1,000,000 passes
Card Formats Supported	ISO standard 7810,7811,7812,7813
Status Indicator	Audible beep for each stripe, successful read
Programming Capabilities	Track selection, Suffix (7 characters max.), Field selection, Start and end sentinel, LRC selection, Inter-character delay, Inter-scan code delay, RS232 parameters (baud rate)
System Compatibilities	S232C interface (IBM AT compatibles), USB interface (USB port on IBM AT compatibles), Keyboard wedge interface (IBM AT, PS/2)
Interface	RS232, PS/2 keyboard, USB-KB (USB keyboard mode), USB-RS232 (USB RS232 mode)
Power	Operating: max 100 mA, while idle: 30 mA
Dimensions	115 mm x 46 mm x 34 mm (WxHxD)
Weight	100 g
Colour	Black and White



Your Dealer