ScanPal EDA70

Enterprise Tablet

The ScanPal[™] EDA70 is Honeywell's enterprise-ready tablet providing real-time connectivity for business-critical applications and efficient data capture capabilities inside or outside of four walls. A sleek, lightweight, enterprise-grade rugged tablet built on the Android[™] 7 (Nougat) platform, the ScanPal EDA70 tablet is ideal for scan-intensive workflows such as customer engagement, on-demand delivery, and field-service applications requiring a truly mobile office. It provides reliable access to communication and information, smooth multi-task processing, and an enterprise level of reliability, protection, future scalability, and lower total cost of ownership.

With the ScanPal EDA70 tablet, network connectivity is no longer a barrier to the benefits of high-performance mobile applications. The ScanPal EDA70 tablet is designed to support the most advanced connected mobile user experiences by facilitating large file transfers, video streaming, and remote access to business applications quickly, so workers can more effectively manage a wide variety of tasks.

The ScanPal EDA70 features a fast processor, 1D/2D barcode scanning, and a built-in camera, plus enough battery life to last a full shift and beyond. This keeps mobile workers always connected to crucial information to place orders, check stock, look up order status, and scan items as they are removed for delivery. A vivid 7-inch Corning® Gorilla® Glass display allows information to be readable in outdoor sunlight conditions. The ScanPal EDA70's design also features a sleek exterior and modern, all-touch interface for a contemporary appearance in customer-facing applications as well as multiple input modes to save valuable time and minimize data entry errors.

A full suite of accessories including desktop charging/docking systems, vehicle cradles, and more is available to keep the ScanPal EDA70 charged and ready for use both inside or out in the field. Hand and shoulder straps are provided for users to hold and handle the tablet easily for long periods of time with less fatigue.

FEATURES & BENEFITS



Installed with Android 7 (Nougat) operating system with GMS to provide smooth system operation to support multi-task operating requirements.



Large, 7-inch Corning Gorilla[®] capacitive high-durability touchscreen is readable both indoors and outdoors, and can be used even with wet hands.



Integrated and easy-to-use, industrygrade imager that provides aggressive scanning of linear and 2D barcodes to increase productivity and throughput.



A sleek, modern, and contemporary design plus enterprise-grade ruggedness. Built tough to withstand 1.2 m (4 ft) drops to concrete, and 200 (0.5m) tumbles; IP64 seal rating against dust and water spray.



802.11a/b/g/n and 4G LTE support ensures robust high speed network connection in external and/or interwork network environments.



Honeywell's enterprise-class 7-inch tablet, the ScanPal EDA70, delivers real-time connectivity, fast data capture capabilities, and an enterprise level of reliability and protection.

ScanPal EDA70 Technical Specifications

| MECHANICAL | |
|--------------------------|---|
| DIMENSIONS (L X W X H) | 214 mm x 118 mm x 21 mm (8.4 in x 4.6 in x 0.83 in) |
| WEIGHT | 550 g (1.21 lb) with battery pack |
| ENVIRONMENTAL | |
| OPERATING TEMPERATURE | -10 °C to 50 °C (-14 °F to 122 °F) |
| STORAGE TEMPERATURE | -20 °C to 60 °C (-4 °F to 148 °F) |
| HUMIDITY | 10 % to 90 % relative humidity (non-condensing) |
| DROP | 1.2 m (4 ft) to concrete at room temp (10 °C to 50 °C) per MIL-STD 810G |
| TUMBLE | Exceeds 200 times at 0.5 m (1.64 ft) per IEC 60068-2-32 specification |
| ESD | ±12 KV Air and ±8 KV Direct |
| ENVIRONMENTAL SEALING | IP64 (IEC 60529) |
| SYSTEM ARCHITECTURE | |
| PROCESSOR | 1.2 GHz Qualcomm MSM8916 quad-core |
| OPERATING SYSTEM | Android 7.1 Nougat |
| MEMORY | 2 GB RAM, 16 GB Flash |
| DISPLAY | 7-inch high definition (1280 x 720) bright color LCD with backlight, outdoor viewable, optically bonded to touch panel |
| TOUCH PANEL | Rugged, multi-touch capacitive touch panel, optically bonded for extra durability and better sunlight viewability. Automatic detection and configuration utilizing mutual and self-capacitance modes for water rejection and use |
| KEYPAD | On-screen keypad, side scan triggers, volume up/down, power button |
| AUDIO | Built-in speaker, Bluetooth® wireless headset support |
| I\O PORTS | Custom I\O connector |
| CAMERA | 5.0-megapixel color camera with autofocus |
| SENSORS | Ambient light sensor, proximity sensor, accelerometer |
| STORAGE EXPANSION | User-accessible microSD card up to 32 GB (SDHC/SDIO-compliant) |
| BATTERY | Li-Ion, 3.8 V, 4000 mAh with integrated battery diagnostics |
| HOURS OF OPERATION | 8+ hours |
| DECODE CAPABILITIES | 1D/2D barcode symbologies |
| APPLICATION SOFTWARE | Honeywell power tools and demos, Honeywell SDKs for Android |
| WARRANTY | One-year factory warranty |

| WIRELESS CONNECTIVITY | |
|---------------------------------|--|
| WWAN | GSM & EDGE: B2/B3/B5/B8 WCDMA: B1/B2/B4/B5/B8 FDD-LTE (4G): B1/B2/B3/B4/B7/B20 |
| WLAN | IEEE 802.11 a/b/g/n; Wi-Fi certified |
| WLAN SECURITY (ANDROID) | OPEN, WEP, WPA/WPA2 (personal and enterprise) |
| SUPPORTED EAP | TLS, PEAP, TTLS, PWD, FAST, LEAP |
| BLUETOOTH | Class 2 V, 4.0 Bluetooth |
| SUPPORTED BLUETOOTH PROFILES | HFP, PBAP, A2DP, AVRCP, OPP only |
| NFC | Integrated Near Field Communication |
| VOIP | Supported |
| VPN | IPSec V4/L2TP, PPTP |
| GPS SUPPORTED PROTOCOLS | GNSS receiver for Beidou, GPS, and GLONASS |

For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road Fort Mill, SC 29707 honeywell.com Corning[®] and Gorilla[®] Glass are registered trademarks of Owens Corning Intellectual Capital, LLC Bluetooth[®] is a registered trademark of Bluetooth SIG, Inc. ScanPal[™] is a trademark or registered trademark of Honeywell International Inc. in the United States and/or other countries. Android[™] is a trademark of Google Inc.

EDA70 Datasheet DS-A4 | A | 09/17 © 2017 Honeywell International Inc.

