




Glancetron 15-LCD - B

Fulfilis all ergonomic demands

- LCD TFT display (active matrix) in 4:3 aspect ratio
- Integrated touch screen; resolution: 1024 x 768 pixels
- Response time of 8 ms
- Optionally available with waiter's lock
- Complete with stand, power supply, cables, touch pen, etc.

Specifications

Display	Screen diagonal / type	38.1 cm (15") / LCD TFT active matrix
	Aspect ratio	4:3
	Resolution (max.)	1024 x 768 Pixel
	Active area (WxH)	304 x 228 mm
	Response time	8 ms
	Colours	16.2 million
	Contrast	600:1
	Brightness	210 cd/m ²
	Viewing angle (H/V)	140° / 150°
	Video Input	VGA (analogue)
	Touch technology	Resistive (5-wire)
General	Touch interface	USB
	Colour	Black
	Dimensions (WxHxD)	367 x 312 x 90 mm
	Weight	4,2 kg
	Power supply	External power supply (DC 12 V)
	Power consumption	Operating: 36 W / Sleep: 4 W / Standby: n/a
	Mounting options	Stand, VESA (75 x 75 mm)
	Control buttons	Power on/off, Menu, Auto, Left/Right, Select
	Audio	Yes
	Certifications	CE, FCC, ROHS, WEEE
	Drivers	Windows 7, Vista, XP, 2000, ME, 98; Linux
Environment	Options	Waiter's lock (Dallas)
	Delivery contents	Monitor, stand, connection cables (USB, VGA, audio), power supply, power cord (EU), touch pen, cleaning cloth, driver CD
	Operating temperature	0 to 50 °C
	Storage temperature	n/a
	Operating humidity	10 to 85 % (non-condensing)
	Lufffeuchtigkeit (Lagerung)	n/a



Your partner