

# METAPACE

## Metapace L-42D - Powerful label printer

[www.metapace.com](http://www.metapace.com)

### Highlights

- Direct thermal label printer for high throughput
- Max speed: 178 mm/sec. at 203 dpi
- Triple interface; ZPL, ZPLII, EPL, EPLII
- Everything included: power supply, connection cable, cleaning pen, design software, etc.
- Optionally available: peeler, auto cutter, Wi-Fi dongle, 300 dpi version

### Technical specifications

#### Print

Printing method	Direct thermal
Print width	max. 108 mm
Print length	6 – 1000 mm
Print speed	max. 178 mm/sec.
Resolution	8 dots/mm (203 dpi) / 12 dots/mm (300 dpi) (optional)

#### Media

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	25 – 110 mm
Roll diameter	max. 130 mm
Core diameter	25.4 – 38.1 mm
Media strength	0.06 – 0.2 mm

#### Electronics

Memory	Flash: 128 MB, RAM: 64 MB DDR2
Interfaces	USB 2.0, Serial, Parallel, Ethernet (option), WiFi (option)
Power supply	AC 100V – 240V, DC 24V, 2,5A
Barcodes	All Standard 1D and 2D Barcodes
Reliability	MCBF: min. 12 months; Auto-Cutter: min. 6 months; TPH: min. 6 months

#### Software

Emulation	EPL, EPL II, ZPL, ZPL II, SLCS
Drivers	Windows 2000, XP (32/64 Bit), 2003 Server (32/64 Bit), Vista (32/64 Bit), Windows 7 (32/64 Bit), Linux (v. 2.4.8 or above), Mac OS (v. 10.4 or above)
Labeldesigner	Metapace Label Designer Software

#### Specifics

Options	Auto-Cutter, Dispenser, Ethernet, WiFi, external media holder
---------	---

#### Warranty

Period	24 months
--------	-----------

#### Housing

Dimension (WxHxD)	194 × 243 × 171 mm
Weight	2.2 kg

**UNPACK &  
GET STARTED**  
Triple Interface Integrated



**L-42D**  
**METAPACE**