

METAPACE

Metapace T-25 – Affordable top-quality POS printer

www.metapace.com

Highlights

- Robust receipt printer for retail and hospitality
- Paper buffer for 10 cm receipt rolls
- Maximum print speed: 250 mm/sec.
- Integrated auto cutter for up to 1 million cuts
- Complete package with drivers, cables, power supply and much more

Technical specifications

Print

Printing method	Direct thermal
Print speed	Max. 250 mm/s
Consumables	Thermal paper
Paper	Width: 58 / 80 mm/s, max. Ø: 102 mm
Print width	45 / 72 mm
Paper supply	Easy-load
Resolution	8 dots/mm (203 dpi)
Character size	Font A: 12 x 24 / font B: 9 x 24
Barcodes	All standard 1D barcodes & PDF 417

Electronics

Emulation	ESC / POS
Sensor	Paper near end, paper end, cover open
Memory	512 KB ROM
Power supply	External, 100–240 V AC, 24 V DC
Reliability	100 km TPH, 1,000,000 cuts, 60,000,000 lines

Interfaces

I/F Ports	USB, RS232, 1x drawer kickout (RJ12)
-----------	--------------------------------------

Software

Operating system	Windows XP, Vista (32 / 64-bit), 7 (32 / 64-bit), 8 (32 / 64-bit)
------------------	---

Housing

Dimensions (WxDxH)	142 x 212 x 149 mm
Colour	Black

Warranty

Period	2 years
--------	---------

Specifics

Package contents	USB cable (A/B), PSU + power cord (EU), CD (drivers, utilities), QSG, test receipt roll
------------------	---

Direct Thermal
**RECEIPT
PRINTER**



T-25

METAPACE